· · · · · · · · · · · · · · · · · · ·	?.,·	NER RECORDATION CERTIL cirement of Act 74; Mich. P.A.	
For corners in SECTION Baraga (County)	_ Located In:	Corner Code #	RECEIVED FOR RECORD THIS 14TH DAY JANUARY A. D. 1999 AT 10:30 A. M. AND RECORDED IN LIBER 5 OF LAND
Public Land Survey	T <u>52N</u> R <u>33W</u> TR TR TR	#13) West MC for the westernmost crossing of the Sturgeon River	CORNER RECORDATION RECORDS ON PAGE 33.
2. Property Controlling S in Section S. Miscellaneous S Property in Sec. S	TR TR TR TR	between A-11 and B-11	BARAGA COUNTY REGISTER OF DEEDS Register of Deeds Stamp & File Number
4. Lot No, Records 5. Private Claims	ed Plat		ABCDEFGHIJKL
that under requirements of P.A. 74, Nabove were in conformance with resurvey instructions of the United Stardecree of a Court of Law and /or the conformance with the rules of the Miestablished, re-established, monument	Wichigan P.A. of 1970, the co gulations and rules therefore tes Department of the Interior at the corner points mention chigan Roard of Land Survey	orner points mentioned in lines 1 and as required in the current manual r. Bureau of Land Management or by led in lines 3, 4 and 5 above were	of (8 5
NOTE: Not more than 2 corners, all on this certificate.	in the same town and range	, may be recorded	8 -19 -20 -21 -22 -23 -24
			10 30 20 20

A. Description of original monument and accessories and/or subsequent restoration: MC #13; West Meander Corner for the westernmost crossing of

the Sturgeon River between A-11and B-11, T52N, R33W; Originally established during U.S. Survey conducted by William Burt, D.S. in 1849 and monumented with a white ash post witnessed by an

S14°W 36 lks. This corner is not indicated in the field notes of a survey of the north line of section 31 conducted by persons unknown for Andrew and Joseph Lescelius on 5 September 1933.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MC #13; West Meander Corner for the westernmost crossing of the Sturgeon River between A-11 and B-11, T52N, R33W;

This corner was considered lost and reestablished on line at the proportionate distance between the NW corner of section 31 and the N% corner of section 31. This corner position falls approximately 106 feet west of the left (west) bank of the Sturgeon River. A witness corner was established on the section line at a distance of 89.00 feet easterly of the proportioned meander corner. This witness corner is located approximately 17 feet west of the water's edge.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

MC #13; West Meander Corner for the westernmost crossing of the Sturgeon River between A-11 and B-11, T52N, R33W;

The witness corner described in Part B was monumented with a 1" (I.D.) x 36" galvanized iron pipe with cap stamped as to location set flush with the ground.

Set 7 ^R spike Attit Cartin -	67°W 81°W /est	90.20' 60.19' 91.10' 1.5'
---	----------------------	------------------------------------

All of the above new bearing trees were marked with upper and lower blazes. The lower blaze was scribed "NBT". Both blazes and a band around the tree at the upper blaze were painted red.

APPROVED LAND CORN A. 345 OF 1990 Baraga County

Surveyor's Michigan License No. 39091

200 Oac

OF MICH

MILESKI

PROFESSIONAL

SURVEYOR

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28,

るす

PAGE

REVISED MAY 14,1975 REVISED JAN., 1983

0