

STATE OF MICHIGAN  
COUNTY OF BARRY  
RECEIVED FOR RECORD

DEC 7 3 41 PM '93

Sandy Schondelmayer  
REGISTER OF DEEDS

BARRY COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in:

BARRY COUNTY

(County)

CASTLETON TOWNSHIP

Located In:

Corner Code ##

1. Public Land Survey

T 3 N R 7 W

K-13

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

002120

Register of Deeds Stamp & File Number

I, ROBERT R. CARR, in a field survey on OCTOBER 14, 19 93,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

K-13 G.L.O. BECH 6" N58-1/2°E 48 LKS.  
G.L.O. SUGAR MAPLE 7" N38°W 09 LKS.  
L.C.R.C. NO. 251 RECORDED 3/20/78.  
M-DOT 11/15/90 FOUND 3/4 IRON AS PER L.C.R.C. NO. 251.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-13 FOUND 3/4" IRON AS PER L.C.R.C. NO. 251 WITH ALL WITNESSES REMAINING.  
ACCEPTED AS CAREFUL PERPETUATION OF CORNER.  
REPLACED 3/4" IRON WITH STANDARD BARRY COUNTY REMON STAKE AND CAP.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-13 BARRY COUNTY REMON 3/4" STEEL ROD AND ALUMINUM CAP WITH CENTER PUNCH.  
NAIL AND SPOTTER IN NORTH SIDE OF 24" MAPLE S37°W 29.32 FEET.  
NAIL AND SPOTTER IN EAST SIDE OF U-POLE N47°E 24.15 FEET.  
FACE OF NW CORNER PORCH FOUNDATION S10°E 43.01 FEET.  
TOP NUT OF FIRE HYDRANT N48°W 32.31 FEET.  
RAIL ROAD SPIKE EAST 25.68 FEET (NE CORNER SECTION 2, T2N, R7W)

SURVEY &  
REMONUMENTATION

APR 05 1994

COMMISSION



Signed by Robert R. Carr  
Surveyor's Michigan License No. 20704

Date NOV. 10, 1993