

SURVEY &
REMONUMENTATION

FEB 03 1999


SECTION

Barry County Remonumentation

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Barry (County)	Located In:	Corner Code #
1. Public Land Survey	T4N R 9W	H-8 (Cen 1/4 cor Sec.22)
	T R	Irving Twp.
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	



2712
Page: 1 of 1
12/15/1998 08:24A
Sandy Schondelmayer - Barry Co. LORCR
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Steven Koerber, in a field survey on Jan 5, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:
H-8 GLO- Post not set by GLO
1. AD Rork Aug 17, 1866
Set post
B. Oak 18 N68°E 58 1/2
Do. 12 S18 3/4E 58 1/2

2. Barry Co. Rd. Comm.
1962 Road plans
NW corner Town Hall SE 51.4'
Flag pole S45°W 46.7'
Cor. Post N45°W 35.4'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-8 Found gear spline
NE corner fndn. of town Hall building S40°W 81.1'
Face of wood corner fence post NW 36.7'
Calculated intersection of 1/4 lines 0.10' North and 4.13' West of monumented position

ACT 345 BARRY COUNTY REMONUMENTATION
APPROVED BY PEER REVIEW AT A MEETING HELD ON

JAN 12, 1998 BR
BRIAN REYNOLDS COUNTY SURVEYOR

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-8 Replaced gear spline with Barry Co. Mon. (3/4" x 24" Iron Rod with cap)
NE corner fndn. of Town Hall building S40°W 81.1'
Spike in n. side 48" Oak S75°E 113.60'
PK nail in N. side light pole S50°W 71.98'
Street sign post N75°E 51.3'



Signed by Steve Koerber
Surveyor's Michigan License No. 39085

Date 12-10-1998