

REMON. COR. A-4, WILLIAMS TWP.
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

SECTION

For corners in
Bay _____
(County)

Located in: Corner Code #

1. Public Land Survey

T 14N R 3E A-4

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, JERRY L. JONES, in a field survey on June 17, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned on lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|---|----|----|----|----|----|----|---|---|---|---|---|---|
| 2 | | 6 | 5 | 4 | 3 | 2 | 1 | | | | | | |
| 3 | | | | | | | | | | | | | |
| 4 | | 7 | 8 | 9 | 10 | 11 | 12 | | | | | | |
| 5 | | | | | | | | | | | | | |
| 6 | | 18 | 17 | 16 | 15 | 14 | 13 | | | | | | |
| 7 | | | | | | | | | | | | | |
| 8 | | 19 | 20 | 21 | 22 | 23 | 24 | | | | | | |
| 9 | | | | | | | | | | | | | |
| 10 | | 30 | 29 | 28 | 27 | 26 | 25 | | | | | | |
| 11 | | | | | | | | | | | | | |
| 12 | | 31 | 32 | 33 | 34 | 35 | 36 | | | | | | |
| 13 | | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:

A-4 W 1/4 Corner of Section 7

Not Established in Original Government Survey
Survey by D. Whittier, 1972, used corner as 1.65' North of Midland Co. corner
Survey by J. Jones, 1990
Survey by L. McGinnis, 1993

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-4 1/4 Corner common to Section 7 on West townline

Set mag nail per survey by D. Whittier 1.65' North of Midland Co. corner. (M-4, T14N-R2E)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-4 1/4 Corner common to Section 7 on West townline.

Replace mag nail with 5/8" rod and brass cap stamped Bay County Remonumentation PS 19838 and set mon box and is accepted a the best available evidence of the position of the accepted corner.

S 80 Deg E, 18.12', pk nail in mail box post
N 20 Deg E, 114.76', pk nail in power pole
S 85 Deg E, 31.65', centerline top fire hydrant
S 20 Deg E, 146.50', pk nail in power pole
South 1.65', Midland Co. corner M-4, T14N-R2E

Signed by Jerry L. Jones
Surveyor's Michigan License No. 19838

Date 12/22/99

Form approved by Michigan State Board of Land Surveyors, Jan. 28, 1971
Revised May 14, 1971
Revised Jan., 1983



APPROVED LAND CORNER
P.A. 345 OF 1990 - Bay County
Date 8.05.99
MM
Michael MacDonald P.S.
County Representative

004 291