

**BAY COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in SECTION

<u>BAY COUNTY</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>14N</u> R <u>5E</u>	<u>PC #5</u>
	T <u>  </u> R <u>  </u>	<u>  </u>
	T <u>  </u> R <u>  </u>	<u>  </u>
	T <u>  </u> R <u>  </u>	<u>  </u>
2. Property Controlling in Section	S <u>20E</u> T <u>  </u> R <u>  </u>	<u>  </u>
	S <u>  </u> T <u>  </u> R <u>  </u>	<u>  </u>
3. Miscellaneous Property in Sec.	S <u>  </u> T <u>  </u> R <u>  </u>	<u>  </u>
	S <u>  </u> T <u>  </u> R <u>  </u>	<u>  </u>

*Barker Foster*  
REGISTER OF DEEDS  
BAY COUNTY, MICHIGAN

2000 JAN -7 P 2:01

RECORDED

Register of Deeds Stamp & File Number

4. Lot No.           , Recorded Plat           

5. Private Claims           

I, DALE L. WINIECKE, in a field survey on NOVEMBER 3, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

PC #5  
CORNER SOUTH OF E-7  
POST SET BY J. MULLETT, JUAN 1839  
12" BUR OAK N50°W, 2.56 CHAINS

CERTIFICATE OF SURVEY L. 676, P. 477, 1972, L. McGINNIS, PS#18999, NO CALL.

PLAT OF MRS. E.P. BIRNEY'S ADDITION TO WENONA, L. 2, P. 12, BAY COUNTY RECORDS.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

PC #5  
MEANDER CORNER SOUTH OF E-7  
SEARCHED THE APPARENT LOCATION OF THE MEANDER CORNER AND FOUND NO MONUMENTATION.  
NO RECORD OF THE CORNER WAS FOUND.  
CORNER RESET USING GLO DISTANCE (30.50 CH) 2013.0' FROM E-7 ON A LINE ESTABLISHED 33' FROM THE EAST LINE OF STATE STREET AS SHOWN ON THE PLAT OF MRS. E. P. BIRNEY'S ADDITION TO WENONA AND THE SURVEY RECORDED IN L. 676, P. 477, L. McGINNIS, PS #18999, 1972.  
THE CORNER FALLS UNDER THE WEST APPROACH OF THE LIBERTY BRIDGE OVER THE SAGINAW RIVER.  
POSITION ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

PC #5  
MEANDER CORNER SOUTH OF E-7

SET 5/8" X 24" REROD WITH BAY COUNTY REMONUMENTATION CAP.  
S48°E 167.55' SOUTHWEST CORNER METAL BUILDING.  
S25°W 297.20' TO THE CENTERLINE OF THE INTERSECTION OF CHAIN LINK FENCES.  
WEST 62.40' TO CHAIN LINK FENCE.  
N60°E 42.45' TO THE SOUTH END OF THE WEST FACE OF THE SOUTH MOST BRIDGE PILLAR, FOURTH RIGHT-OF-WAY FROM WEST BRIDGE ABUTMENT.  
N40°W 40.13' TO THE SOUTH END OF THE EAST FACE OF THE THIRD BRIDGE PILLAR NORTH, THIRD RIGHT-OF-WAY FROM WEST BRIDGE ABUTMENT.

Signed by *Dale Winiecke*  
Surveyor's Michigan License No. 41915

Date 12/30/99

FB WT 1999, P. 14

APPROVED LAND CORNER  
P.A. 345 OF 1990 - Bay County  
Date 11/02/99  
HM  
Michael MacDonald P.S.

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 197  
REVISED MAY 14, 197  
REVISED JAN., 198  
REVISED OCT., 199

005 12