BAY COUNTY REMONUMENTATION

SECTION LAND CORNER RECORDATION CERTIFIC SECTION Filing Requirement of Act 74, Mich. P.A.		
BAY COUNTY Located In: Corner Code #	2000 JAN - Barden For REGISTER BAY COUNT	REC
1. Public Land Survey	7 P 2: Whichigan	RECORDED
in Section S T R	Register of Deeds St	
4. Lot No, Recorded Plat	ABCDEFG	ніјкь
5. Private Claims	2 6 5 4	3
I, <u>DALE L. WINIECKE</u> , in a field survey on <u>NOVEMBER 11</u> , 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:		-15 - 1413242525
NOTE: Not more than 2 corners, all in the same Town and Range, may be recorded on this certificate.	11	-27 - 26 - 253635363
A. Description of original monument and accessories and/or subsequent restoration: PC #8 MEANDER CORNER EAST OF E-7 POST SET BY J. MULLETT, JUNE 1839 10" BUR OAK N71 1/2°W, 5.48 CHAINS		
B. Description of corner evidence found and/or method applied in restoring or reestablishi	ng corner:	•
PC #8 MEANDER CORNER EAST OF E-7 SEARCHED THE APPARENT LOCATION OF THE MEANDER CORNER AND FOUND NO MONUMENTA' NO RECORD OF THE CORNER WAS FOUND. CORNER LOCATION DETERMINED USING GLO DISTANCE (21.82 CH) 1440.12' FROM E-7 ON A LII EXTENDED. THE CORNER FALLS IN THE WATER AT WHEELERS MARINA. POINT WAS MOVED WE DISTANCE FROM E-7 TO THE WITNESS POINT FOR THE MEANDER CORNER IS 1303.31'. POSITIOI LOCATION OF THE ORIGINAL CORNER.	NE ESTABLISHED FROM D-7 TI STERLY TO THE EDGE OF THE N ACCEPTED AS A WITNESS F	MARINA, THE POINT TO THE
C. Description of monument for corner and accessories established to perpetuate locating	the position of the corners	Herrettheeps
C. Description of monument for corner and accessories established to perpetuate locating PC #8 WITNESS CORNER TO MEANDER CORNER MEANDER CORNER EAST OF E-7 SET 5/8" x 24" REROD WITH BAY COUNTY REMONUMENTATION CAP. N 60°E 18.45' TO THE CENTERLINE OF FIBERGLASS LIGHT POST FOR BOAT SLIPS 78/79. N 20°W 37.88' TO THE CENTERLINE OF FIBERGLASS LIGHT POST FOR BOAT SLIPS 80/81. S 60°E 41.75' TO THE CENTERLINE OF FIBERGLASS LIGHT POST FOR BOAT SLIPS 76/77. N 40°E 18.90' TO THE NORTH EDGE OF WOOD BOARDWALK. S 40°W 7.25' TO THE NORTH EDGE OF ASPHALT PARKING LOT.	ı yı ş Pi	DALE L. WINIECKE TOTESSIGNAL SURVEYOR No. 41915
Signed by Dell Winell	ate 12/30/99	ESSIONA
Surveyor's Michigan License No. 41915		
FB W-T 1999, P.25 FORM APPROVED BY MIC	HIGAN STATE BOARD OF PROFESSIONAL S	SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975 REVISED JAN., 198 REVISED OCT., 199

