

RATIFIED BY THE BERRIEN COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER MICHIGAN
PUBLIC ACT 345 OF 1990

08/24/94

111#1725

A33

CORNER

\$7.00

08/24/94

111#1725

A33

STATE REMON FEE \$2.00

BERRIEN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Berrien
(County)

Located In:

Corner Code ##

- | | | | | | |
|-------------------------|---|-----------|---|------------|------------|
| 1. Public Land Survey | T | <u>3S</u> | R | <u>18W</u> | <u>M-3</u> |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling | S | | T | | |
| in Section | S | | T | | |
| 3. Miscellaneous | S | | T | | |
| Property in Sec. | S | | T | | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, V.J. Strebs, in a field survey on 16 August, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1827 - William Brookfield, G.L.O.
Beech 16 - S54 $\frac{1}{2}$ °W - 16 - Links
Beech 16 - N62 $\frac{1}{2}$ °W - 50 - Links

1883 - Luther Hemingway
Found Corner

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Iron Rod in Monument Box over iron in Monument Box

SURVEY &
REMONUMENTATION

SEP 15 1994

COMMISSION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Pulled Iron Rod
Set 1"x3 ft Iron pipe with B.C.R.P. Brass Cap in Monument Box
S.W. Corner of Block Bldg. - N40°E - 55.20'
Nail & Witness Tag in Power Pole (B-102.16) - N45°W - 84.64'
Nail & Witness Tag in Power Pole (B-111-76) - S45°W - 65.62'
Brass Cap on Monument Box (A-3) - South - 58.66'



Signed by V.J. Strebs
Surveyor's Michigan License No. 26469

Date 18 August 1994