

BERRIEN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

AUG 30 3 39 PM 1994

8-18-94
For corners in

Berrien (County)	Located in:	Corner Code ##
1. Public Land Survey	T 5 R 19	I-6
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Bernice T. Thibault
REGISTER OF DEEDS
BERRIEN COUNTY MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Charles W. Barger, in a field survey on August, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

March 1830 - John Mullett set half mile Post
W. Oak 12 S2E 47
Pine 14 N81W 12

08/30/94

111#2164 A66
CORNER \$9.00
111#2164 A66
STATE REMON FEE \$2.00

* Additional documentation on Sheet #2.

08/30/94

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-6 - 1/2" capped rebar
Hydrant N64°W 30.6'
Power Pole B279-229 N62°E 23.25'
Power Pole B279-109 S09°E 111.0'
Telephone Pedestal N66°E 33.3'
Telephone Pedestal S88°W 38.0'

SURVEY &
REMONUMENTATION

SEP 15 1994

COMMISSION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-6 - 1" Pipe 36" Long with 2 1/2" Remonumentation Brass Cap in Monument Box
Hydrant N64°W 30.6'
Power Pole B279-229 N62°E 23.25'
Power Pole B279-109 S09°E 111.0'
Telephone Pedestal N66°E 33.3'
Telephone Pedestal S88°W 38.0'

And is accepted as a careful and faithful
perpetuation of the position of the original
corner.

Signed by Charles W. Barger P.S.

Date August 29, 1994

Surveyor's Michigan License No. 31589

MARCH. 1830	John Mullett L2. P184 Government Notes
	Set Half Mile Post W. Oak 12 S2E 47 Pine 14 N81W 12
JANUARY. 1972	N. Berndt
	Found Spike Hydrant NW 30.7 P. Pole NE 23.3 30" Maple SE 27.0
May. 1976	M. Rushlow
	RR Spike Power Pole N 50 E 23.10 Top of Hydrant N 50 W 30.61 26" Maple S 60 E 26.48
AUGUST. 1977	M. Rushlow
	RR Spike Fire Hydrant N 60 W 30.70 Utility Pole N 60 E 23.10 NW Cor. HSP. S 65 E 86.50 26" Maple S 60 E 26.48
APRIL. 1978	M. Rushlow
	RR Spike Iron Pipe East 33.0 Fire Hvd. N 65 W 30.65 Tele. Pole West 25.0
AUGUST. 1978	M. Rushlow
	RR Spike Fire Hydrant N 60 W 30.70 Utility Pole N 60 E 23.10 26" Maple S 60 E 26.48
APRIL. 1979	M. Rushlow
	RR Spike Iron Pipe East 33.0 Fire Hydrant N 65 W 30.65 Tele. Pole West 25.0
FEBRUARY. 1981	J. Kamer
	RR Spike Top of Fire Hvd. N 66 W 30.65 PK S. Face of PP N 60 E 22.95 Iron Pipe East 33.00
FEBRUARY. 1983	C. Barger
	1/2" Capped Rebar Hydrant N 64 W 30.6 Power Pole B-279-229 N 62 E 23.25 Conc. Monument West 33.0 Power Pole B-279-109 S 9 E 111.0
1984	V. J. Streps
	RR Spike Mon. West 40.0 I. P. East 33.0 Nut on hvd. N 60 W 30.68
APRIL. 1984	J. Kamer
	Found 1/2" Capped Rebar Hydrant N 64 W 30.62 Power Pole B-279-229 N 62 E 23.25 Conc. Monument West 33.01 Power Pole B-279-109 S 9 E 110.96
OCTOBER. 1984	J. Kamer
	Found 1/2" Capped Rebar Hydrant N 64 W 30.62 Power Pole B-279-229 N 62 E 23.25 Conc. Monument West 33.01 Power Pole B-279-109 S 9 E 110.65
MAY. 1994	C. Barger
	1/2" Capped Rebar Hydrant N 64 W 30.6 Power Pole B 279-229 N 62 E 23.25 Power Pole B 279-109 S 09 E 111.0 Telephone Pedestal N 66 E 33.3 Telephone Pedestal S 88 W 38.0