

RAISED BY THE BERRIEN COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER MICHIGAN
PUBLIC ACT 345 OF 1990

SURVEY & REMONUMENTATION

APR 26 1995

RECORDED

BERRIEN COUNTY REMONUMENTATION PROGRAM

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

DEC 2 11:11 AM '94

For corners in

Berrien
(County)

Located in:

Corner Code #

1. Public Land Survey

T 6 S. R 17 W.

F-3

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Berrien County
REGISTER OF DEEDS
BERRIEN COUNTY, MICHIGAN

12/02/94 111W8049 A99
Register of Deeds Stamp & File Number 7.00

12/02/94 111W8049 A99

STATE REMON FEE \$2.00

I, R.L. Harner, in a field survey on November 30, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F-3

Government - post

Poplar 18" N. 62° W. 62 links

W. Ash 24" N. 61° E. 62 links

Berrien County Road Commission

corner fence post North 23.0'

corner fence post South 24.3'

6" Oak S.E. 21.8'

6" Pear N.W. 46.3'

6" Cedar N.E. 33.0'

6" Cedar N.E. 40.8'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-3

found rail road spike

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-3

set iron and brass cap in monument box

P.K. nail in power pole North 44.00'

nail and washer in 10" Maple South 29.75'

nail and washer in fence post N. 48° W. 60.31'

nail and washer in 6" Maple S. 48° W. 51.80'

*Accepted as a careful and faithful perpetuation of
the position of the original corner.

Signed by

Date

30 Nov 1994

Surveyor's Michigan License No. 22436

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971;
REVISED MAY 14, 1971;
REVISED JAN., 1981

LIBER

3 PAGE 201