

SURVEY &
REMONUMENTATION
DEC 08 1993
COMMISSION

11/29/93

CORNER 111#2893

A33
\$7.00

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

Berrien County Remonumentation

FOR CORNERS OF-- <u>Berrien</u> <u>COUNTY</u>	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>8</u> N. S., R. <u>17</u> E. W.		<u>L-9</u>
2. PROPERTY CONTROLLING IN SECTION <u>24</u> , T. <u>8</u> N. S., R. <u>17</u> E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

RECORDED

NOV 29 2 09 PM '93

I, Robert W. Prestine, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on OCT. 29, 1993, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

L-9 NOT SET by GOUT (on STATE LINE)
3/4" COR. Sec. 24 GOUT. Survey 1827 W.M. Brookfield D.S.
Jim Dewey R.L.S. fd. Stone 1941 NO WITS
SET Prop Line East 16.5'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

L-9 Found iron & stone, from survey of 1973
By R.W. Prestine, Stone fd. 1941 By Jim Dewey R.L.S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-9 removed iron & set 3/4"x36" pipe & Berrien Co.
remonumentation Cap bent over stone & set
Mon. Box.
nail & washer in W. side 21" OAK N26°E 17.73'
" " " S. side 19" W. OAK N68°E 26.48'
" " " W " Elec. Pole S28°E 37.78'
" " " E " " " S56°W 67.88'
13.5' S. of & STATE LINE Rd. & CONST.
3/4" iron East 16.5'
1/2" iron West 66.0'
ratified by peer group 11-8-93

SIGNED BY Robert W. Prestine DATE Nov. 29 - 83

SURVEYOR'S MICHIGAN REGISTRATION NO. 18662

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

