

SURVEY & REMONUMENTATION

MAR 13 1998

SECTION

BRANCH COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

BRANCH _____ Located In: _____ Corner Code # _____
(County)
GIRARD TWP.
1. Public Land Survey T 5 S R 6 W E-1
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

STATE OF MICHIGAN
Branch County
Recorded

10-22-1997 09:56:01

Linda Lee Morrison-Mathews
REGISTER OF DEEDS

Liber 000003 Page 0159

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, EDWARD W. REED, in a field survey on JULY 18, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
NORTHWEST CORNER SEC. 4 - NORTHEAST CORNER SEC 5

1825: WM BROOKFIELD, DEPT SURVEYOR - SET CORNER
1892: ID MINER, CO SURVEYOR - FOUND STONE
1971: E.R.REED, CO SURVEYOR - FOUND STONE, SET 3/4" IRON ROD ON TOP,
SET CI-MONUMENT BOX

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4" IRON ROD IN MONUMENT BOX, REPLACED IRON WITH 1/2" X 18" REBAR IRON AND REMON CAP, RAISED CI-MONUMENT BOX TO ROAD SURFACE WITH RINGS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
1/2" REBAR IRON IN CI-MONUMENT BOX

P. POLE, N6W 35.32' TO NAIL & SPOTTER
TEL. PED, N61W 49.15'
SE CORNER GARAGE # 295, N12W 93.96'
40" MAPLE, S28W 55.96' TO NAIL & SPOTTER
2.7' NORTH OF C/L OF EAST-WEST ROAD

ACCEPTED BY THE BRANCH COUNTY
SURVEY PEER GROUP AS THE OFFICIAL
CORNER UNDER MICHIGAN PUBLIC ACT 345
OF 1990 AT A MEETING HELD ON
9-10-97

E.R. Reed, P.S. Co. Rep.
E.R. REED

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER

Signed by

EDWARD W. REED

Date JULY 18, 1997

Surveyor's Michigan License No. 33985

