

SURVEY &
REMONUMENTATION

FEB 08 1999

SECTION

BRANCH COUNTY REMONUMATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

BRANCH COUNTY
BUTLER TWP.

Located in:

Corner Code #

1. Public Land Survey

T 5 S R 5 W

C-7

T R

T R

T R

2. Property Controlling
in Section

S T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

STATE OF MICHIGAN
Branch County
Recorded

11-04-1998 15:46:09

Linda Lee Morrison-Mathews
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

ACCEPTED BY THE BRANCH COUNTY
SURVEY PEER GROUP AS THE OFFICIAL
CORNER UNDER MICHIGAN PUBLIC ACT 345
OF 1990 AT A MEETING HELD ON
9-09-1998

E.R. Reed, Co. Rep.
E.R. REED

4. Lot No. , Recorded Plat

5. Private Claims

I, EDWARD W. REED, in a field survey on MAY 6, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

QUARTER CORNER COMMON TO SECTIONS 17, 18, 19, AND 20

A. Description of original monument and accessories and/or subsequent restoration:

1825: R. CLARK, JR., D.S. - CORNER SET

1964: C.B. WOOD, SURVEYOR, SURVEY TIED TO CORNER

1978: E.R. REED, COUNTY SURVEYOR, FOUND IRON USED BY "MYSELF" IN 1958, RECORDED IN L.C.R.C. #217

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2 x 12" IRON FITTING WITNESS OF L.C.R.C. #217

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1/2" X 18" REBAR IRON WITH REMONUMENTATION CAP IN CI-MONUMENT BOX FLUSH WITH PAVED ROAD SURFACE

METAL ANCHOR POST

S50W 38.8'

FACE OF TELEPHONE PEDESTAL

N30W 54.4'

EAST OF N-S CMP ROAD CULVERT

63.9'

CENTER OF TELEPHONE PEDESTAL

S65W 40.2'

FACE OF POWER POLE

S42E 74.1'

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

Edward W. Reed

EDWARD W. REED

Date

9-9-98

Liber 000003 Page 0211

Surveyor's Michigan License No. 33985

