

SURVEY &
REMONUMENTATION

FEB 08 1999

SECTION

BRANCH COUNTY REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

BRANCH COUNTY QUINCY TWP	Located In:	Corner Code #
1. Public Land Survey	T 6 S R 5 W	C-3
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S	
	T R	
3. Miscellaneous	S	
	T R	
Property in Sec.	S	
	T R	

STATE OF MICHIGAN
Branch County
Recorded:

11-04-1998 15:47:07

Linda Lee Morrison-Mathews
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

ACCEPTED BY THE BRANCH COUNTY
SURVEY PEER GROUP AS THE OFFICIAL
CORNER UNDER MICHIGAN PUBLIC ACT 346
OF 1990 AT A MEETING HELD ON

7-29-98
E.R. Reed Co. Rep.
E.R. REED

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, EDWARD W. REED, in a field survey on JULY 14, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 5-6-7-8

A. Description of original monument and accessories and/or subsequent restoration:
1829: O. RISDON, D.S - CORNER SET
1935: E.L. MINER, CO SURVEYOR - SET 1" X 24" GAS PIPE IN DEPOSIT OF BRICK BATS @ PRORATED DISTANCE.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1" X 24" GAS PIPE IN A DEPOSIT OF BRICK BATS

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET ½" X 18" REBAR IRON AND REMON CAP IN CI-MONUMENT BOX 4" BELOW GRAVEL ROAD SURFACE

3" WOOD FENCE POST	SOUTH	24.5' TO FACE
14" TWIN APPLE	N 22 W	38.7' TO CENTER
18" MAPLE	N 60 E	59.4 TO CENTER
3" WOOD FENCE POST	S 54 W	36.8' TO FACE

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Edward W. Reed
EDWARD W. REED

Date 9-9-98

Surveyor's Michigan License No. 33985

Liber 00003 Page 0219

