

FEL 11 2000

SECTION

BRANCH COUNTY REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
Branch County
Recorded

For corners in

12-30-1999 11:03:37

Linda Lee Morrison-Mathews
REGISTER OF DEEDS

Liber 00004 Page 0069

Register of Deeds Stamp & File Number

BRANCH COUNTY Located In: Corner Code #
BRONSON TWP

1. Public Land Survey T 7 S R 8 W C-3
T R
T R
T R
2. Property Controlling S T R
in Section S
T R
3. Miscellaneous S
T R
Property in Sec. S
T R

4. Lot No. , Recorded Plat

5. Private Claims

I, EDWARD W. REED, in a field survey on OCT 21, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 5, 6, 7, & 8

A. Description of original monument and accessories and/or subsequent restoration:

1826: WM. BROOKFIELD, D.S., CORNER SET
1881: CHAS. HAMILTON, CO. SURVEYOR, SURVEY
1866: A.R. DAY, DEP. CO. SURVEYOR, SURVEY "STONE" WITH BRICKS BURIED AROUND IT

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND POINTED GRANITE STONE WITH BRICK AROUND
SET 1/2" X 18" REBAR OVER 3/4" X 30" REBAR WITH REMON CAP IN CAST IRON MONUMENT BOX 4" BELOW GRAVEL ROAD

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1/2" X 18" REBAR WITH REMON CAP IN CAST IRON BOX
EAST IN LINE WITH FENCE
EAST 27.9' RR TIE ANCHOR POST
WEST 60.8' CENTER OF 24" OAK
S40E 78.8' 10" TWIN OAK

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Edward W. Reed

Date OCT. 21, 1999

EDWARD W. REED

Surveyor's Michigan License No. 33985

ACCEPTED BY THE BRANCH COUNTY
SURVEY PEER GROUP AS THE OFFICIAL
CORNER UNDER MICHIGAN PUBLIC ACT 345
OF 1990 AT A MEETING HELD ON
DEC. 07, 1999

E.R. Reed, P.S.
E.R. REED

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

