

SURVEY &
REMONUMENTATION

JAN 23 1996

BRANCH COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN

Branch County

Recorded

09-28-1995 10:19:52

Linda Lee Morrison-Mathews
REGISTER OF DEEDS

Liber 000003 Page 0020

Register of Deeds Stamp & File Number

For corners in

COMMISSION

BRANCH

(County)

Located In:

Corner Code #

GILEAD TWP.

1. Public Land Survey

T 8S R 7W

C-2

2. Property Controlling
in Section

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Edward W. Reed, in a field survey on June 20, 19 95,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

QUARTER CORNER COMMON TO SECTIONS 5 & 6, T8S, R7W, GILEAD TWP., BRANCH COUNTY, MI.

1828: Robert Clark, Jr., D.S.-set corner

1869: A. R. Day-stone and brick

1949: H. L. Russell, County Surveyor,-survey tied to corner

1959: E. R. Reed-Plat of "Kralls Subdivision" tied to corner

1976: David Boone-survey tied to corner

1981: E. R. Reed, County Surveyor,-recorded L.C.R. #II-048, 5/8" iron rod over stone

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron over stone

Set remonumentation cap and cast iron monument box flush with road surface

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

N30°W 58.0'-SE corner of Thompson monument

S81°W 43.4'-to NE corner base of Cranson monument

S46°W 65.2'-to NE corner base of Spring monument

S20°W 121.3'-steel anchor post on S line of cemetery

Set .7" W of center line of road

And is accepted as a careful and faithful
perpetuation of the position of the original corner.

Signed by

Edward W. Reed

33985

Date

June 20, 1995

Surveyor's Michigan License No.

ACCEPTED BY THE BRANCH COUNTY
SURVEY PEER GROUP AS THE OFFICIAL
CORNER UNDER MICHIGAN PUBLIC ACT 345
OF 1990 AT A MEETING HELD ON
9-13-95

E. R. Reed, Co. Rep.

