

APPROVED

Date 7-21-99 RRC

CALHOUN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

CALHOUN COUNTY  
REMONUMENTATION.

CALHOUN	Located In:	Corner Code #
(County)		
CONVIS TOWNSHIP		
1. Public Land Survey	T <u>1S</u> R <u>6W</u>	<u>B-13</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling	S _____ T _____ R _____	_____
in Section	S _____ T _____ R _____	_____
3. Miscellaneous	S _____ T _____ R _____	_____
Property in Sec.	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

STATE OF MICHIGAN  
CALHOUN COUNTY  
RECORDED

27 JUL 1999 10:26:39 AM

ANNE B. NORLANDER  
CLERK - REGISTER OF DEEDS

LIBER 2147 PAGE 710  
Register of Deeds Stamp & File Number

I, ROBERT R. CARR, in a field survey on JUNE 25, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. CORNER SET BY SYLVESTER SIBLEY D.S. IN 1826.  
ROBERT R. CARR P.S. NO. 20704, 1998 SET CORNER AT INTERSECTION OF NORTH  
AND SOUTH 1/4 LINE FENCE WITH SOUTH LINE OF SECTION 36.

SURVEY &  
REMONUMENTATION

MAR 13 2000

SECTION

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

REPLACED IRON I SET IN 1998 WITH STANDARD CALHOUN COUNTY REMONUMENTATION  
MONUMENT IN CASTING.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

BERNTSEN MONUMENT IN CASTING:  
14" MAPLE N 15°E, 23.88' (NAIL AND SPOTTER)  
UTILITY POLE S 01°E, 59.12' (NAIL AND SPOTTER)  
16" HICKORY S 58°E, 56.32' (NAIL AND SPOTTER)  
16" MAPLE N 72°E, 66.82' (NAIL AND SPOTTER)  
IN LINE WITH FENCE LINE RUNNING NORTH  
CENTER LINE OF ROAD 2.5' SOUTH

THIS LOCATION IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by [Signature]

Date 7-21-99

Surveyor's Michigan License No. 20704 ROBERT R. CARR

