

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Calhoun

(County)
Sheridan Twp.

Located In:

Corner Code ~~##~~

- | | | | | | | | |
|---------------------------------------|---|---|---|---|---|---|------|
| 1. Public Land Survey | T | 2 | S | R | 4 | W | K-13 |
| | T | | | R | | | |
| | T | | | R | | | |
| | T | | | R | | | |
| 2. Property Controlling
in Section | S | | T | | R | | |
| | S | | T | | R | | |
| 3. Miscellaneous | S | | T | | R | | |
| Property in Sec. | S | | T | | R | | |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Donald J. Davis, in a field survey on August 17, 1995, 19_____,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Original survey in 1825 by Lyon. (no witnesses remain).

1" iron set in concrete pvmtn in 1938 by Barry, RLS #2258 for plat of Section 36.
(pavement)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Dug thru 6" of bituminous paving at point set from old plat corners.

Found 1" iron 8" long in concrete pavement.

Accepted as good perpetuation of corner location.

REMONUMENTATION

FEB 22 1996

COMMISSION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Berntsen monument in monument box at point.

Nail & Tag utility pole S 40° W 84.75'

Nail & Tag utility pole N 20° W 54.89'

Nail & Tag utility pole N 15° E 109.33'

Nail & Tag utility pole N 80° E 82.36'

APPROVED

Date Sept. 20 1995
CALHOUN COUNTY
REMONUMENTATION
CALHOUN COUNTY
RECORDED

22 SEP 95 10:00 A.M.

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

LIBER 1822 PAGE 28

Signed by Donald J. Davis
Surveyor's Michigan License No. 17617

Date September 15, 1995

