

REMONUMENTATION

FEB 22 1996

COMMISSION

CALHOUN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

APPROVED  
Date Sept 20 1995  
CALHOUN COUNTY  
REMONUMENTATION.

For corners in

CALHOUN (County)	Located In:	Corner Code ##
BATTLE CREEK CITY		
1. Public Land Survey	T 2 S R 8 W	C-4
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

STATE OF MICHIGAN  
CALHOUN COUNTY  
RECORDED

22 SEP 95 10:02 A.M.

ANNE B. NORLANDER  
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7	8		9		10		11		12			
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

ROBERT R. CARR, in a field survey on SEPTEMBER 1, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

1. Description of original monument and accessories and/or subsequent restoration:

E 1/4 POST SECTION 7, TOWN 2 SOUTH, RANGE 8 WEST.  
ORIGINAL CORNER SET BY S. SIBLEY, 1826.  
F. HODGEMAN 1889; SET TILE FROM ORIGINAL BEARING TREE.  
L.C.R.C. BY W. CRANE, SEPTEMBER 9, 1991, LIBER 1583 PAGE 549.

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND REMAINS OF TILE INSIDE 4" IRON PIPE BESIDE REMAINS  
OF 1 FT SQUARE CONCRETE FENCE POST.

LIBER 1822 PAGE 31

2. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

LEFT 4" IRON PIPE WITH TILE INSIDE IN PLACE AND PLACED CARSONITE WITNESS POST 1.0 FT WEST.  
NAIL & SPOTTER IN SOUTH SIDE OF 12" OAK S89°E 43.03 FEET  
NAIL & SPOTTER IN NORTHEAST SIDE OF 12" OAK N49°W 41.20 FEET.  
NAIL & SPOTTER IN SOUTHWEST SIDE OF 10" OAK S41°E 77.80 FEET.  
NAIL & SPOTTER IN SOUTHEAST SIDE OF 18" OAK S38°W 63.39 FEET.



Signed by Robert R. Carr  
Surveyor's Michigan License No. 20704

Date SEPTEMBER 20, 1995