

APPROVED

ate Oct. 18 1995
CALHOUN COUNTY
REMONUMENTATION.

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
CALHOUN COUNTY
RECORDED

12 JAN 96 10:25 A.M.

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

LIBER 1839 PAGE 652

Register of Deeds Stamp & File Number

Calhoun (County)	Located In:	Corner Code ##
City of Battle Creek (B.C. Twp.)		
Public Land Survey	T <u>2</u> S R <u>8</u> W	<u>E-7</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
Property Controlling	S _____ T _____ R _____	_____
in Section	S _____ T _____ R _____	_____
Miscellaneous	S _____ T _____ R _____	_____
Property in Sec.	S _____ T _____ R _____	_____

Lot No. _____, Recorded Plat _____
Private Claims _____

Donald J. Davis, in a field survey on March 6, 1995,
hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

Description of original monument and accessories and/or subsequent restoration:

Original survey in 1826.
Resurvey tile set in 1886 by Hodgeman.
10" White Oak N 47° E 29 links.
7" White Oak S 24° W 42 links.

LCRC recorded July 12, 1995 in Liber 1810, page 7,
for Plat of Jacaranda Woods No. 2 by Davis.

Tile found by De Keyser in 1963.
12" Apple South 14.05'
8" Poplar East 7.42'
8" Poplar North 17.15'

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found iron over tile.

Accepted as true corner.

REMONUMENTATION

FEB 22 1996

COMMISSION

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Berntsen monument.
Nail & Tag 8" Oak N 65° E 45.85'
Nail & Tag 24" Oak North 61.40'
Nail & Tag RR tie corner Post S 30° E 22.00'
Nail & Tag Oak West 35.20'



igned by Donald J. Davis
urveyor's Michigan License No. 17617

Date January 8, 1996