APPROVED CALHOUN COUNTY REMONUMES

CALHOUN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN CALBUM COUNTY RECORDED

L M

For corners in Fredonia Township Calhoun County		Located In: Corner Code #				17 DEC 1999 2:32:42 PM											
1. Public Land Survey	ı	T 3S T	R <u>6W</u>	G-1		ANNE B. MORLANDER CLERK - REGISTER OF DEEDS											
		T	R			L'BE	R 2	18	5	PAGE	98	17					
2. Property Controlling In Section	s s		R			ļ											
3. Miscellaneous Property in Sec.	\$ \$	T	R			R	egis	ter	of D	eeds	Star	np.	& Fil	e N	um	ıbe	•r
4. Lot No, Reco	orded Plat				<u> </u>	А	В	c	D :	E F	G	н	1		ĸ	L	
I, Scott E. Koch, in a field survey 74, Michigan P.A. of 1970, the or regulations and rules therefore States Department of the Interior that the corner points mentione Michigan Board of Land Survey monumented, recovered, found	corner points as required or, Bureau o d in lines 3, eyors or by	mentioned in the cur of Land Ma , 4 and 5 : a Degree	d in lines 1 a rrent manua inagement d above were	and 2 above were in conforma at of survey instructions of the or by decree of a Court of Lav in conformance with the rule	nce with e United w and/or	ĺ	- 6 - 7 -18		8	9	_	-	1	ļ	-		
NOTE: Not more than 2 corne on this certificate	ers, all in the	e same to	wn and ran	ge, may be recorded		7 8	19-	1	20	-21		22	2	3	-	 24	

SURVEY & REMONUMENTATION

12

MAR 1 3 2000

SECTION

SCOTT E.

KOCH

PROFESSIONAL

December 1, 1964 - Plat of Wildwood Meadows L. 17 of Plats, on Page 6. William Hume Rogers - Shows the corner on the plat with the GLO falling from G-13

a W. Oak 9 in. diam. \$371/2°W, 73 lks. (48.18') dist. & a W. Oak 8 in. diam. S661/2°W, 62 lks. (40.92') dist.

A. Description of original monument and accessories and/or subsequent restoration:

November 1825 - G.L.O. Lucius Lyon, Set Post 39.74 ch. (2622.84') North of East 1/4 Post

Marshall Twp., but gives no description of, or witnesses to the corner. It also gives a distance of 2624.00' to G-2.

August 1971 - Milton DeKeyser, 1" Pipe.

12" Oak - S15°W, 23.30'

Conc. Pipeline Marker - \$30°E, 60.78'

Intersected the N. boundary 67 lks. (44.22 ft.) E. of post

Set Post Cor. to Secs. 3&4 from which

NW Cor. House – SE, 121.43' SW Cor. Garage – 167.47'

28" Basswood - N30°E, 26,48"

12' NW of NW Edge of Pvm't.

May 9, 1998 - Scott E. Koch, PS #41103,

In an unrecorded survey by Ledy Survey Group, Project No. 98.0649, calls for a found 1" Pipe, but gives no witnesses. It does give a distance of 43.96' to a clay tile marking G-13 of Marshall Twp, also a distance of 2621.38' to G-2.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Searched at the apparent location of the corner and found a 1" Pipe at the approximate PI of 15 Mile Road on fenceline to the West. Pipe matched DeKeyser witnesses' to House & Garage. Dug to a depth of 3'± and found several small stones. Accepted pipe as the best evidence of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner of Mich.

Replaced 1" Pipe with Standard BernTSEN Monument stamped Calhoun Co. Remon. & PS 41103.

NE'ly face of Concrete Cas Line Marker, \$209M, 62.10" STORT STORT

NE'ly face of Concrete Gas Line Marker, S20°W, 62.10'

Calhoun Co. Remon. Monument stamped "GROAT" at G-13 Marshall Twp., Due West, 43.84' Northwest Corner of House #11966, S45°E, 121.43'

Southwest corner of Garage #11966, S30°E, 167.47

Scatt E. KM

Date November 16, 1999

41103 POFESSION!

Surveyor's Michigan License No.

41103

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN. 1993 REVISED OCT., 1995