

APPROVED

MAR 30 1999

Date 12-9-98 RRC  
CALHOUN COUNTY  
REMONUMENTATION.

CALHOUN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

CALHOUN

(County)

Located in:

Corner Code #

1. Public Land Survey

T 3S R 8W

B-5

T      R     

T      R     

T      R     

2. Property Controlling  
in Section

S      T      R     

S      T      R     

3. Miscellaneous  
Property in Sec.

S      T      R     

S      T      R     

4. Lot No.     , Recorded Plat     

5. Private Claims     

I, ROBERT R. CARR, in a field survey on OCTOBER 26, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1/4 CORNER COMMON TO SECTIONS 7 & 8

A. Description of original monument and accessories and/or subsequent restoration:

ORIGINAL CORNER SET BY ROBERT CLARK, D.S. 1826

HODGMAN, RESURVEY 1885, CORNER LOST, FROM CORNER OF 7, 8, 17 & 18  
RAN WEST 40.00, SET TEMPORARY STAKE, 79.23 TO SECTION CORNER,  
EAST CORRECTED 38.89, SET POST WITH STONES AROUND

A.H.C. WITNESS CARD, NO DATE, TILE?, 5/8" BOLT IN BLACKTOP.

ROBERT CARR, P.S. #20704, 1993, FOUND 3/4" IRON PIPE, ONE A.H.C. WITNESS REMAINING.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4" PIPE PER CARR ABOVE, ONE A.H.C. WITNESS REMAINING  
(SOUTHWEST CORNER OF HOUSE FOUNDATION, N70°E 101.9 FEET)

DUG AND FOUND HODGMAN TILE IN STONES 0.55 FEET EAST AND  
0.32 FEET SOUTH OF 3/4" PIPE.

PLACED BERNTSEN MONUMENT IN MONUMENT BOX OVER TILE AND STONES.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

BERNTSEN MONUMENT IN MONUMENT BOX OVER TILE  
SOUTHWEST CORNER OF HOUSE FOUNDATION, N70°E 101.20 FEET  
UTILITY POLE, S20°E 65.73 FEET ( SET SPOTTER )  
40" MAPLE, N28°W 64.88 FEET ( SET SPOTTER )  
8" WOOD CORNER POST, S40°W 43.30 FEET ( SET SPOTTER )  
IN CENTERLINE OF ROADS N&S, E&W

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT  
OF THE POSITION OF THE ORIGINAL CORNER.

Signed by



Date DECEMBER 8, 1998

Surveyor's Michigan License No. 20704

ROBERT R. CARR

STATE OF MICHIGAN  
CALHOUN COUNTY  
RECORDED

15 DEC 1998 3:41:06 PM

ANNE D. NORLANDER  
CLERK - REGISTER OF DEEDS

LIBER 2087 PAGE 946

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5			4		3		2		1	
3													
4	7		8			9		10		11		12	
5	0												
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

