

MAR 3 0 1999

APPROVED

Date 12-9-98 RRL
CALHOUN COUNTY
REMONUMENTATION.

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

CALHOUN (County)	Located In:	Corner Code #
LEROEY TOWNSHIP		
1. Public Land Survey	T <u>3S</u> R <u>8W</u>	<u>E-8</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

STATE OF MICHIGAN
CALHOUN COUNTY
RECORDED

15 DEC 1998 3:40:44 PM

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

LIBER **2087** PAGE **944**

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, ROBERT R. CARR, in a field survey on JULY 16, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1/4 POST COMMON TO SECTION 20 AND 21

A. Description of original monument and accessories and/or subsequent restoration:

THE ORIGINAL CORNER WAS SET BY ROBERT CLARK, D.S. 1826

HODGMAN, RESURVEY 1885, FOUND POST AT INTERSECTION OF FENCES
250 LKS SOUTH OF WET PRAIRIE, SET POST (TILE) NO TREES NEAR FOR WITNESSES.


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND ANGLE IRON FENCE CORNER POST IN CONCRETE, DUG AROUND IT FOR TILE,
BUT DID NOT FIND, POST IS SET IN BED OF ROCKS
MEASURED 2673.84 EAST TO 1/2" IRON AT CENTER OF SECTION AND
2647.17 FEET NORTH TO FOUND NORTHWEST CORNER OF SECTION.
ACCEPTED ANGLE IRON AS BEST REMAINING EVIDENCE OF CORNER.
LEFT ANGLE IRON POST IN PLACE, NO OTHER MONUMENT SET.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

2" ANGLE IRON POST SET IN CONCRETE AND ROCKS
20" HICKORY, N47°W 13.90 FEET (SET SPOTTER)
24" HICKORY, S45°W 5.32 FEET (SET SPOTTER)
18" OAK, S83°W 29.50 FEET (SET SPOTTER)
8" CHERRY, S15°W 26.26 FEET (SET SPOTTER)
130' ± SOUTH OF WATERS EDGE TO NORTH

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by 
Surveyor's Michigan License No. 20704 ROBERT R. CARR

Date DECEMBER 7, 1998

