

APPROVED

Date 8-17-94
CALHOUN COUNTY
REMONUMENTATION.

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Calhoun

(County)

Located In:

Corner Code M-4

1. Public Land Survey

T 3 S R 8 W

M-4

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

STATE OF MICHIGAN
CALHOUN COUNTY
RECORDED

18 AUG 94 12:08 P.M.

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Donald J. Davis, in a field survey on August 10, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Tile set in resurvey of 1884 by Hodgeman.

Road construction destroyed tile.

Iron rod set for corner by R. Carr by running East line and setting corner on line
at $\frac{1}{2}$ distance.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found iron rod set by Carr.

Accepted as restoration of original corner.

LIBER 1763 PAGE 759

SURVEY &
REMONUMENTATION

OCT 24 1994

COMMISSION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Berntsen monument in monument box at location.

Nail & Tag 30" Oak West 63.65'

Nail & Tag Utility Pole S 10° W 121.10'

Nail & Tag 20" Oak East 119.40'

Nail & Tag 12" Pine S 60° E 149.80'



Signed by

Donald J. Davis

Date August 17, 1994

Surveyor's Michigan License No. 17617