

SURVEY &
REMONUMENTATION
APR 06 1995
COMMISSION

STATE OF MICHIGAN
CASS COUNTY
RECEIVED FOR RECORD

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

CASS COUNTY REMONUMENTATION

1994 DEC 28 PM 1 47

orners in
ASS

(County)

Located In:

Corner Code ##

Public Land Survey

T 6 S R 16 W

T R

T R

T R

Property Controlling

S 18 T 6 S R 16 W

Section

S T R

Miscellaneous

S T R

Property in Sec.

S T R

A-6

North meander cor.

Ann L. Hinmons
CLERK/REGISTER

LIBER 2 PAGE 377

Register of Deeds Stamp & File Number

Ratified by Peer Group

In Accordance With P.A. 345

Chairman *Dale C. Bahr*

Date *Nov 22, 1994*

Lot No. , Recorded Plat

Private Claims

Robert W. Prestine

in a field survey on June 27, 19 94

reby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
s 1 and 2 above were in conformance with regulations and rules therefore as required in the
nt manual of survey instructions of the United States Department of the Interior, Bureau of Land
gement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
of Law; established, re-established, monumented, re-monumented, recovered, found as
ssed below:

Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

Description of original monument and accessories and/or subsequent restoration:

A-6 North meander corner on West side of Section 18

Govt.

Set post Wm. Brookfield, March 1828

51.00 chains North of SE corner, Section 13, T. 6 S., R. 17 W.

Black oak 18" N 80 1/3° W 26 links

Black oak 16" N 74 1/2° E 78 links

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

SURVEY &
REMONUMENTATION

MAY 16 1997

COMMISSION

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Did not find corner. Set at prorated distance from SE corner, Section 13, T. 6 S., R. 17 W.,
Govt. = 61.00 chains = 4026.0'. Set at 4026.55'. Total miles measures 5280.72'
In Section 13 on Section line. (County line)

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Berrien County remonumentation monument, also recorded in Berrien County Liber 3, page 121
Mail & witness tag in South side 28" Ash N 70° E 11.70'
Mail & Witness tag in East side 6" Maple S 8° E 21.78'
Mail & witness tag in North side 13" Wild Cherry S 32° W 45.53'
Mail & witness tag in South side 20" Maple N 79° W 27.80'
Edge of marsh South 49' ±

by *Robert W. Prestine*

Date December 27, 1994

or's Michigan License No. 18662

