

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey	T	42N	R	2E	89
	T		R		
	T		R		
	T		R		
2. Property Controlling	S		T	R	
in Section	S		T	R	
3. Miscellaneous	S		T	R	
Property in Sec.	S		T	R	

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Aug 30 2005

I, Stephan J. Szyszkoski, in a field survey on _____, 19_____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(89) Quarter corner common to Sections 19 and 30. 1845 - Established by John Mullett, Deputy Surveyor: East corrected between Sections 19 & 30 ...42.08 Set qr. Section post. Tamarack 8 N57E 8 links, Tamarack 6 S5E 10 links. ...82.08 Section corner.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(89) The original post and accessories were not recovered. Found no acceptable evidence of the position of the original corner on the ground. Reestablished the corner by single proportionate measurement to the original record and on line between monumented Section corners 2652.77' east and 2790.71' west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(89) Set 1"IDx36" I.pipe with 4" alum.
MDNR cap. Set measuring nails in:
10" Spruce S65E 10.85' mrd "1/4S NBT"
5" Balsam N32W 12.6' do
8" Balsam N61E 27.05' do
8" Balsam N04E 29.57' do
Bearings are magnetic. Distances are to
nail with tag.



Signed by

Stephan J. Szyszkoski

Date

1/10/06

Surveyor's Michigan License No. 33986
For the Michigan Department of Natural Resources