

SURVEY &
REMONUMENTATION

CHIPPEWA COUNTY REMONUMENTATION CORNER

APR 26 1995

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION

For corners in
Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey

T44N R 1W I-1

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims



\$ 7.00 LAND CORNER

\$ 2.00 MSSR

5 DEC 94 12:33 P.M. RECEIPT# 1520

RECEIVED FOR RECORD

CHIPPEWA COUNTY - STATE OF MICHIGAN

SHARON H. KENNEDY, REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Keith R. Waters in a field survey on May 25, 19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

I-1 Corner Common to Sections 2 & 3, on North Boundary of T44N, R1W.
(Closing Corner on Township Line)

Original ties to post: Birch 10, S48°E 37 links
Sugar 10, S19°W 14 links

1962 - Corner recorded in liber 3, page 128, Chippewa County corner records,
B. Buckler, RLS, 8887. Set 1" pipe and with 4" aluminum cap. Witness:
14" Red Oak, S41°W 127 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-1 (T44N, R1W)

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a bent 1" pipe east of found standard corner on the north side of a 2-track road to the west at the intersection of a 2-track road to the south, bearing tree is gone. Buckler's corner form indicates that he established closing corner at record G.L.O. distance (20 links) east of the standard corner. Removed bent pipe and set a 3/4" rebar and aluminum cap on the township line 13.20 feet east of the standard corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-1 (T44N, R1W)

Corner is 3/4" x 24" rebar with 3/4" aluminum Chippewa County Remonumentation cap on north side of 2-track road west at 2-track road south.

Witnesses:

8" Oak, S37°W 36.39'

9" Oak, S58°W 41.85'

11" Oak, 17°W 30.53'

9" Sugar Maple, N67°E 21.95'

3/4" Rebar w/aluminum cap

(Standard Corner), WEST 13.20'

Note: Distances are to a nail and tag in the side of the witness object. Trees are blazed and painted. Bearings are compass bearings corrected for declination.

Signed by

Keith R. Waters

Date

12-1-94

Surveyor's Michigan License No.

33142

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

