

1993

93 DEC -3 PM 3: 58

COMMISSION

For corners in
 Chippewa

(County)

Located in:

Corner Code --#

1. Public Land Survey

T 45N R 1E A-10 Same
 T 45N R 1W M-10 Corner

2. Property Controlling
 in Section

S T R

3. Miscellaneous
 Property in Sec.

S T R
 -S T R

J. Roger Malott
 REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
 5. Private Claims

I, Keith R. Waters in a field survey on July 29, 19 93,
 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
 in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
 current manual of survey instructions of the United States Department of the Interior, Bureau of Land
 Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
 Court of Law; established, re-established, monumented, re-monumented, recovered, found as
 expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
 on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-10 (T45N, R1E)

1/4 Corner Common to Section 30, T45N, R1E & Section 25, T45N, R1W.

Michigan State Highway Department (11-29-65) as recorded in liber 3, page 221,
 of Chippewa County corner records: Found 1/2" reinforcing rod in monument box
 with the following ties: 8" Twin Elm, N65°E 72.31'
 8" Elm, S40°W 75.14'
 Fence Post, N75°W 76.12'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-10 (T45N, R1E)

This corner is being perpetuated as part of the Chippewa County
 Remonumentation Program.

Found a 1/2" iron pin in a monument box approximately 0.5' east of centerline
 of Highway M-129. All witnesses from Highway Department records are gone.
 Distances to Section corners 1/2 mile north and 1/2 mile south check closely
 with Highway Department records. Accepted corner as found and established
 four new witness objects.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-10 (T45N, R1E)

Corner is a 1/2" iron pin in a monument box 0.5' east of centerline of Highway
 M-129. Witnesses:

Power Pole, N58°E 91.94'
 10" Balsam Fir, N83°E 100.37'
 6" Red Maple, S78°W 87.18'
 Telephone Pole, N60°W 79.45'

Note: Distances are to a nail and tag in
 the side of witness object. Trees are
 blazed and painted. Bearings are compass
 bearings corrected for declination.
 Distances measured with EDM.

Signed by Keith R. Waters

Date 11-30-93

Surveyor's Michigan License No. 33142