

**SURVEY &
REMONUMENTATION**

CHIPPEWA COUNTY REMONUMENTATION CORNER

APR 26 1995

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION

For corners in
Chippewa

Located In:

Corner Code #

1. Public Land Survey

T 45N R 1W L-11

2. Property Controlling
in Section

S T

3. Miscellaneous
Property in Sec.

S T

4. Lot No. , Recorded Plat

5. Private Claims



\$ 7.00 LAND CORNER

\$ 2.00 MSSR

19 JAN 95 4:19 P.M. RECEIPT# 2266

RECEIVED FOR RECORD

CHIPPEWA COUNTY - STATE OF MICHIGAN
SHARON H. KENNEDY, REGISTER OF DEEDS

Register of Deeds Stamp & File Number

Keith R. Waters

August 4

19 94

I, Keith R. Waters, in a field survey on August 4, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-11 1/4 Corner Common to Sections 25 & 36, T45N, R1W.

Original ties to post: Sugar 20, N61°E 43 links Sugar 4, S14°W 23 links.
1982 - As recorded in liber 6, page 135, Chippewa County corner records, by William L. Karr, P.S. 27450, set 1/2" iron w/cap mid-way on line between sections corners east and west.

1992 - As recorded in liber 8, page 296, Chippewa County corner records, by Neil E. Hill, P.S. 27447. Found 1/2" iron as recorded in liber 6, page 135. Set monument box over found iron.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-11 (T45N, R1W)

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a 1/2" iron in a monument box approximately 1 foot north of the centerline of Tone Road (M-80). Offset iron with witness hubs prior to re-construction of Tone Road. Monument box is to be placed in spring, 1995.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-11 (T45N, R1W)

Corner is a 3/4" x 24" rebar with a plastic Chippewa County Remonumentation cap in a monument box to be placed in spring, 1995. Witnesses:

PK Nail in Power Pole, S67°E 144.42'

PK Nail in Power Pole, S68°W 116.10'

MDOT Tag in 9" Poplar, N55°E 70.87'

MDOT Tag in 12" Maple, S12°W 69.26'

Note: Bearings are based on MDOT records.

Signed by Keith R. Waters

Date 12-23-94

-Surveyor's Michigan License No. 33142

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

