

JUL 28 1999

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey

T 45N R 2E

B-7/C-7 #2

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

SECTION
RECEIVED FOR RECORD
CHIPPEWA COUNTY
STATE OF MICHIGAN

93 DEC 30 PM 2:46

J. Roger Malott
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Keith R. Waters November 29 1993

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-7/C-7 Witness Corner to Meander Corner Sections 18 & 19, T45N, R2E

Original meander corner was set 28.50 chains (1881 feet) east of 1/4 corner between Sections 18 & 19, T45N, R2E, no witnesses were established.

Corner is shown on "Assessor's Plat No. 1 of Bruce Township" as recorded in liber 15, page 22, of Chippewa County recorded plats (1989) as 1/2" iron pin with cap #27450 at the east end of 15 Mile Road.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-7/C-7 (T45N, R2E)

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a 1/2" iron pin with plastic cap #27450 approximately 4 feet south of the centerline of east-west gravel road (15 Mile Road), approximately 30 feet from the shore of the Saint Marys River. Position checks with other found monumentation in Assessor's Plat No. 1 of Bruce Township. Accepted as found and established witness objects.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-7/C-7 (T45N, R2E)

Corner is a 1/2" iron pin with cap #27450 4 feet south of the centerline of 15 Mile Road, approximately 30 feet from shore of Saint Marys River. Witnesses:

Power Pole w/meter, N81°W 173.13'
Power Pole (DR2-234N), S81°W 84.39'
15" Willow, S51°E 80.46'
Center of Eye Bolt under Navigation
Tripod, N34°E 19.63'

Note: Distance to poles and willow is to a nail and tag in the side. Willow is blazed and painted. Bearings are compass bearings corrected for declination.

Signed by Keith R. Waters

Date 12-30-93

Surveyor's Michigan License No. 33142