

SURVEY & REMONUMENTATION

MAR 09 1994

Chippewa County Remonumentation Corner

RECEIVED FOR RECORD
CHIPPEWA COUNTY
STATE OF MICHIGAN

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC 14 PM 4: 26

COMMISSION

For corners in

Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey

T 46N R 1E

C-5

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

J. Roger Malott
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, William L. Karr, in a field survey on November 23, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(C-5) Section Corner Common to Sections 7, 8, 17 & 18, (T46N-R1E)


This corner was recorded by Keith R. Water, L.S. 33142, in Liber 7, Page 250 of the Chippewa County Corner Records as a 4" diameter concrete monument with the following witnesses:

8" Oak	N43°W	93.00'
4" White Pine	N62°W	232.00'
Fence Post	S07°W	59.80'
Fence Post	S55°E	113.05'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(C-5) This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a 4" diameter concrete monument and witnesses as called for. Accepted monument as found and added one witness.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(C-5) Corner is a 4" diameter concrete monument with 1/8" iron rod 3' North of centerline of Eight Mile Road.

Witnesses: 8" Oak	N43°W	93.00'
4" White Pine	N62°W	232.00'
Fence Post	S07°W	59.93'
Fence Post	S55°E	113.05'
1" Pipe with pinched top	N45°E	45.25'



Signed by William L. Karr Date 12/14/93

Surveyor's Michigan License No. 27450

NOTE: Bearings are compass bearings corrected for declination.

Distances are to a nail in side of witness objects unless noted.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983