

MAR 09 1994

CHIPPewa COUNTY

RECEIVED FOR RECORD
CHIPPEWA COUNTY
STATE OF MICHIGAN

Chippewa County Remonumentation Corner

LAND CORNER RECORDATION CERTIFICATE 93 DEC 14 PM 4: 26
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Chippewa

(County)

Located In:

Corner Code ##

- | | | |
|------------------------------------|------------|-----|
| 1. Public Land Survey | T 46N R 1E | G-2 |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S T R | |
| | S T R | |
| 3. Miscellaneous Property in Sec. | S T R | |
| | S T R | |

J. Roger Mallett
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, William L. Karr, in a field survey on November 30, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(G-2) 1/4 Corner Common to Sections 3 & 4 (T46N-R1E)

1845: James H. Mullett, D.S.

Set Post.

Fir 6 N50°E 14 links
Cedar 10 N05°W 13 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(G-2) This corner is being re-established as part of the Chippewa County Remonumentation Program.


Found no evidence of original corner. County Surveyor notes indicate an overall distance for the mile of 5252' (5250.09 measured today). 2634' for the North 1/2 mile, 2618' for the South 1/2 mile (North tier of Township). There are existing fences to the East and West on the 1/4 lines. Re-established corner on line between closing corner 3/4 and Section corner 3, 4, 9 & 10 and a split of fence lines to East & West. North 1/2 mile measures 2629.40' (2634 C.S.) and South 1/2 mile measures 2620.68' (2618 C.S.)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(G-2) Corner is a 3/4" x 24" iron with stamped aluminum cap (Chippewa County Remonumentation) 3' West of the centerline of Ridge Road.

Witnesses: 3rd Post North of Fence Corner N51°E 52.98'
Power Pole (B27-1/16) S85°E 38.53'
Corner Fence Post S86°W 33.06'
3rd Post North of Fence Corner N60°W 36.28'

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													



Signed by William L. Karr Date 12/14/93

Surveyor's Michigan License No. 27450

NOTE: Bearings are compass bearings corrected for declination.
Distances are to a nail in side of witness objects unless noted.