

MAY 28 1997

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
Chippewa County Remonumentation Corner

For corners in COMMISSION

Chippewa County	Located in:	Corner Code #
1. Public Land Survey	T46N R1E	L-11
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No.		Recorded Plat
5. Private Claims		

\$7.00 LAND CORNER

\$2.00 MSSR

2/28/1997 2:54:29 PM

Receipt #217

RECEIVED FOR RECORD

CHIPPEWA COUNTY - STATE OF MICHIGAN  
SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 9 PAGE 355

Register of Deeds Stamp & File Number

I, William L. Karr, in a field survey on December 2, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(L-11) 1/4 Corner Common to Sections 25 & 36, T. 46 N., R. 1 E.

1845 J.H. Mullett set post in original survey. Original GLO distance on the section line between 25 and 36 was 80.08 chains, (5285.28').

1910 In a field book in County Surveyors Office, a survey of section 36 shows the North line as being 2640' on the East side and 2633' on the West.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(L-11) 1/4 Corner Common to Sections 25 & 36, T. 46 N., R. 1 E.

This corner is being reestablished as part of the Chippewa County Remonumentation Program.

Found no evidence of original corner or subsequent restoration. Reestablished corner from 1910 County Surveyor notes and positioned corner on line between the section corners to the East and West and at a pro-rated County Surveyor distance. Distance to the section corner to the East is 2638.36, and to the West is 2631.37'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(L-11) 1/4 Corner Common to Sections 25 & 36, T. 46 N., R. 1 E.

Corner is a 3/4" x 24" re-bar with plastic Chippewa County Remonumentation Cap. Corner falls on South edge of 11 Mile Road. Corner is set flush with surface.

Witnesses:	8" Triple White Birch	N 46° E	54.06'
	12" Spruce	S 66° E	64.54'
	6" White Birch	S 61° W	55.68'
	10" Double Aspen	N 34° W	50.82'

Bearings are compass bearings, corrected for declination, all distances are to a nail and tag in the side of the witness subject unless otherwise noted.

Signed by William L. Karr

Date 12-30-96

Surveyor's Michigan License No. 27450