

SURVEY & REMONUMENTATION

MAY 28 1997

COMMISSION

For corners in

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Corner \$7.00 LAND CORNER

Chippewa County

Located in:

Corner Code #

1. Public Land Survey

T46N R1E

M-7/ M-8 } Same

T46N R2E

A-7/ A-8 } Corner

T R

Other #1

T R

T R

T R

T R

T R

2. Property Controlling in Section

S

S

S

S

3. Miscellaneous

Property in Sec.

S

S

4. Lot No.

Recorded Plat

5. Private Claims

\$2.00 MSSR

2/28/1997 2:53:31 PM

Receipt #217

RECEIVED FOR RECORD

CHIPPewa COUNTY - STATE OF MICHIGAN

SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 9 PAGE 354

Register of Deeds Stamp & File Number

I, William L. Karr, in a field survey on November 13, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(M-7 / M-8) Meander Corner Common to Section 24, T. 46 N., R. 1 E., and Section 19, T. 46 N., R. 2 E.

1845 J.H. Mullett set post in original survey, 10 chains North of the 1/4 corner.

Witnesses:	Willow 7"	S 47° W	1.63 ch
	Willow 8"	S 86° W	3.19 ch

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(M-7 / M-8) Meander Corner Common to Section 24, T. 46 N., R. 1 E., and Section 19, T. 46 N., R. 2 E.

This corner is being reestablished as part of the Chippewa County Remonumentation Program.

Could find no evidence of the original corner or subsequent restoration.

Reestablished the corner on the extension of the section line to the South at the record GLO distance North from the 1/4 corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(M-7 / M-8) Meander Corner Common to Section 24, T. 46 N., R. 1 E., and Section 19, T. 46 N., R. 2 E.

Corner is a 3/4" x 48" re-rod with stamped aluminum Chippewa County Remonumentation Cap. Corner is set in open marshy area and is 1' above ground.

Witnesses:	Waters Edge	North	120'
	Waters Edge	East	90'
	Wood Post	North	3.00'
	1/4 Corner	S 01° 11' 01" E	660.00'
	Section Corner	S 01° 11' 01" E	3300.00'
	Meander Corner on North Section Line	N 36° 58' 23" W	2433.81'

Bearings are grid bearings based on the Michigan State Plane Coordinate System, North Zone. Distances are actual measured distances to adjacent corners. No other acceptable ties available.

Signed by

Date

12-30-96

Surveyor's Michigan License No. 27450

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

REVISED OCT., 1995

BOOK 9 PAGE 354