

MAR 2 1999

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Corner

For corners in

SECTION

Chippewa County

Located In:

Corner Code #

1. Public Land Survey

T 46N R 2E L-13/M-13 SAME
T 45N R 2E L-1/M-1 CORNER

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

\$7.00 LAND CORNER

\$2.00 MSSR

21 JAN 1999 11:06:19 AM Receipt #13123

RECEIVED FOR RECORD

CHIPPEWA COUNTY - STATE OF MICHIGAN
SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 10 PAGE 371

Register of Deeds Stamp & File Number

I, William L. Karr in a field survey on October 2, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(L-13/M-13) Witness Corner to the Meander Corner Section 36, Township 46 North, Range 2 East, and Section 1, Township 45 North, Range 2 East.

1845: J. Mullett set post Birch 10" N70°W 14.

1920: F.H. Brown references corner as the hub of a mowing machine. Distance West to 1/4 corner 36/1 is 697 feet. Distance West to Section Corner is 3285 feet, Southeast corner barn S43°45'W 503.5 feet

1977: T.M. Kelly, P.S. 24599 found a 1" bolt which matched the tie to the barn. Distance West to Section corner was 3286.62 feet. Corner was recorded in Liber 10, Page 269 of the Chippewa Corner Records.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(L-13/M-13) Witness Corner to the Meander Corner Section 36, Township 46 North, Range 2 East, and Section 1, Township 45 North, Range 2 East. This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found 1" bolt as called for by Kelly and all witnesses. Distance West to Section corner measures 3283.68 feet. Distance West to 1/4 Corner measures 698.16 feet. Accepted the Corner position as found.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

(L-13/M-13) Witness Corner to the Meander Corner Section 36, Township 46 North, Range 2 East, and Section 1, Township 45 North, Range 2 East. Corner is a 1" bolt approximately 95 feet West of the water's edge. (St. Mary's River)

Witnesses:

SW Cabin Corner N30°W 80.85 feet
SE Cabin Corner N05°W 76.25 feet
SE Cabin Corner N82°W 21.85 feet
1/4 Corner Sections 36/1 West 698.16 feet

Signed by William L. Karr

Date 12/22/98

Surveyor's Michigan License No. 27450

NOTE: All bearings are compass bearings corrected for declination. All distances are to a nail and tag in the side of witness object unless otherwise noted.

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995