

1993

CHIPPEWA COUNTY REMONUMENTATION CORNER

RECEIVED FOR RECORD
CHIPPEWA COUNTY
STATE OF MICHIGAN

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC -3 PM 3: 57

For corners in
Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey T 47N R 1W G-7
- T _____ R _____
- T _____ R _____
- T _____ R _____
2. Property Controlling S _____ T _____ R _____
- in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
- Property in Sec. S _____ T _____ R _____

J. Roger Malott
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Keith R. Waters November 3 93

I, _____, in a field survey on _____, 19 _____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-7 Section Corner Common to Sections 15, 16, 21, & 22, T47N, R1W

Original ties to set post
(Wm. A. Burt, D.S., 1840):
Tamarack 12, S30°W 38 links
Spruce 6, N49°E 63 links

Corner is shown on a section subdivision sketch of Section 22, T47N, R1W, done by James L. Fletcher, P.S. 19830, dated 1-8-85.

Corner is also referred to on a land corner recordation certificate, liber 6, page 384, by DNR surveyor Gerald Wiggins, P.S. 23521.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-7 (T47N, R1W)

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a 1/2" iron with plastic cap #19830, approximately 50 feet southeast of the centerline of a snowmobile trail (abandoned Duluth South Shore & Atlantic Railroad). Position fits with section breakdown as shown on Fletcher's sketch. Corner was also used by DNR surveyor Wiggins to set the 1/4 common to Sections 15 & 16, T47N, R1W in 1987. Accepted corner location found. Replaced 1/2" iron with a 3/4" x 48" rebar with a 3 1/4" aluminum Chippewa County Remonumentation cap and established witness objects.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7 (T47N, R1W)

Corner is a 3/4" x 48" rebar with 3 1/4" aluminum Chippewa County Remonumentation cap 50'± southeasterly of the centerline of snowmobile trail.

Witnesses:

- 5" Tamarack, S82°E 11.31'
- 6" White Pine, S29°W 48.06'
- 6" White Birch, N48°W 34.72'
- 8" White Birch, N08°W 44.18'

Note: Distances are to a nail and tag in the side of the witness object. Bearings are compass bearings corrected for declination. Trees are blazed and painted. Distances measured with EDM.

Signed by *Keith R. Waters*

Date 11-30-93

Surveyor's Michigan License No. 33142

