

CHIPPEWA COUNTY REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Chippewa

(County)

Located in:

Corner Code #

1. Public Land Survey

2. Property Controlling
In Section

3. Miscellaneous
Property in Sec.

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

T47N R1W A-10/11
T47N R2W (#3) M-10/11
T_____ R_____ SURVEY &
T_____ R_____ REMONUMENTATION
S_____ T_____ R_____ JUL 22 1999
S_____ T_____ R_____ SECTION

Same
Corner

\$ 7.00 LAND CORNER

\$ 2.00 HSSR

28 FEB 96 4:36 P.M. RECEIPT# 459

RECEIVED FOR RECORD
CHIPPEWA COUNTY - STATE OF MICHIGAN
SHARON H. KENNEDY, REGISTER OF DEEDS

Register of Deeds Stamp & File Number

Keith R. Waters

12/28 95

I, _____, in a field survey on _____, 19____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|---|----|---|----|---|----|---|----|---|----|---|---|
| 1 | | | | | | | | | | | | | |
| 2 | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | | |
| 3 | | | | | | | | | | | | | |
| 4 | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | | |
| 5 | | | | | | | | | | | | | |
| 6 | 18 | | 17 | | 16 | | 15 | | 14 | | 13 | | |
| 7 | | | | | | | | | | | | | |
| 8 | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | | |
| 9 | | | | | | | | | | | | | |
| 10 | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | | |
| 11 | | | | | | | | | | | | | |
| 12 | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | | |
| 13 | | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:

A-10/11 Witness Corner to Meander Corner Between Section 30, T47N, R1W & Section 25, T47N, R2W

845 - Original meander corner established by James Mullett 31.25 chains (2062.5 feet) north of Section corner A-11 was a 6" Maple.
Witnesses: Point of land bears N36.5°E and N34°W.

937 - Rudolph Larsen, Chippewa County Surveyor notes, indicates meander corner was established on the extension of the F.H. Brown line between Sections 25 & 30, 1880 feet north of Section corner A-11, 20 feet from shore.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being re-established as part of the Chippewa County Remonumentation Program.
Found no evidence of corner or its accessories. Re-established corner 1826 feet north of Section corner A-11, on the northerly extension of the line between 1/4 corner A-12 and said Section corner A-11. Corner is approximately 25 feet south of the shoreline Mosquito Bay. Both the original GLO position and subsequent position as established by County Surveyor Larsen now face the water.

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 3/4" x 24" rebar with a 3" aluminum Chippewa County Remonumentation cap approximately 25 feet south of the shoreline Mosquito Bay. Witnesses:
Black Ash, N10°W 8.40'
Black Ash, EAST 5.91'
Black Ash, S22°E 3.61'
Black Ash, S70°W 18.22'

Distances are to a nail/tag P.S. 33142 in the side of the tree. Trees are blazed and painted.
Bearings are compass bearings corrected for declination.

by Keith R. Waters
Surveyor's Michigan License No. 33142

Date December 29, 1995

