

FEB 1 8 1994 CLARE COUNTY REMONUMENTATION PROGRAM

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

	CLARE (County)	Located In:	Corner Code ##
1.	Public Land Survey	T 17N R 6W	C-10
		T R	
		T R	4 · · · · · · · · · · · · · · · · · · ·
	* ,	. T R	
2.	Property Controlling	[*] S T R	
	in Section	S T R	
3.	Miscellaneous	S T R	
-	Property in Sec	STB	i i

Ball Some A Line


Register of Deeds Stamp & File Number

4.	ot No, Recorded Plat
5.	rivate Claims

MARK R. ROBISON , in a field survey on OCTOBER . 19 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration: 1847 ORSON LYON, POST, HEMLOCK 14" N 11%, 43 LKS F BEECH 14" S 41-1/2°E, 31 LKS 4-19-71 LAPHAM, LCRC 2-71



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/8" RE-ROD INSIDE 1-1/2" PIPE, 3' LONG. FOUND RECORDED WITNESSES:

N 47'W, 114.05' - S.E. CORNER BLDG.
S 40'W, 70.55' - POWER POLE

This Corner established in Clare County Remonumentation Program. See dossier for detailed report.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 5/8" X 36" RE-ROD WITH 3" CLARE COUNTY MONUMENT CAP.

N 65°E, 74.2' - 4" OAK S 55°E, 61.0' - 4" PINE N 47°W, 114.05' - S.E. CORNER BLDG. S 40°W, 70.50' - POWER POLE



MARIE C

Date

Surveyor's Michigan License No. .

FORM APPROVED BY MICHIGAN STATE GOARD OF LAND SURVEYORS, JAN. 28, 1871 REVISED MAY 14, 1975 REVISED JAN., 1883