CLARE COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE 96 DEC 23 AM 11: 59

		VEU.	
EU	/] [96	
		96 Musik	

For corners in	riing	Requirement of Act 74	, Mich. P.A. 1	970			R		STER				ı
CLARE (County)	Located In: Corner Code #						Ţ	.13 400	ARE INA	COL M.	INT CAI	Y RR	
1. Public Land Survey	T_17N R_3 T R T R	3W M - 9				-							
2. Property Controlling in Section 3. Miscellaneous Property in Sec.	TR_ STR STR STR_			10 To	Reg	jiste	er of E	eeds	s Sta	mp &	File	Nur	nbe
4. Lot No, Reco	rded Plat								-				
5. Private Claims				1	A B	C	D	E	r g	H	I d	J K	I
				2	— 6	i -	- 5-	-	<u>, </u>		:	<u>-</u>	_
, MARK R. ROBISON	in a field survey on N	ovember 40 05 i i i		3	\dashv	\dashv							
requirements of P.A. 74, Michiga	an P.A. of 1970, the comer i	moints mentioned in lines 4 and	l O mbarra ramas ta		7 	1	8) —	-10	1	1	1
Comormance with regulations and United States Department of the I	rules inerefore as required i Interior, Bureau of Land Man	in the current manual of survey in	nstructions of the	5									-
that the corner points mentioned Board of Land Surveyors or by	l In lines 3. 4 and 5 above we	Fig. in conformance with the rule.	a af tha https://www.	· · ·	—16	,	_1 /	1º		-15	1 	4	—1
recovered, found as expressed be	How:	_aw, established, re-establishe	d, monumented,	8	_19		_20_	2		-22_		3	
NOTE: Not more than 2 corr	ners, all in the same town a	and range, may be recorded		9	_				_	<u></u>			
on this certificate.		3 ,, 10 , 100 , 100		10	j 3(-	_29_	2	8	_27 <u></u>	2	6-	_2:
	•			11	-	-				+			_
				12	—3¦1		_3 ¹ 2	3	3	34	_з	5	—3
A. Description of original mo 1837 HODGSON SET POST IN SWAMP WITCEDAR 10" S27W 17 BLACK ASH 10" N25W 15 1-4-17 C.S.R. (BK. 5, PG. 25) M-9 TO L-9 40,20	12-1 Set Wit. V	and/or subsequent restorat 5-80 MEYERS-UNRECORDED SUR 1/2" C.1. NORTH 18.0 10" POST YEST 17.90 4" BIRCH SOUTH 30.40 FE. COR.		13						•			
B. Description of corner evid FOUND 1/2" X 18" C.I. SET 5/8" X LINE. MEAS. SOUTH 5247.26 TO	36" REROD ON EAST BASE O	od applied in restoring or re F 10" MAPLE. CORNER FALLS IN M-8 & WEST 5337.8 TO K-9. POSIT	LOLD ARANDONE	n ROAN	GR#	ADE T	O WES	IT ANI AST P	D IN N' Per Me	ORTH- YERS	SOUT SUR	H FEI	NCE
			A	.P\$ P(PΑ	. 34	LAM 15 of Col	199		ER			
SEE DOSSIER FOR DETAILED RE	PORT.		Ch	nairma		./	2.1	g/.,	fon	L_	_		
				do		•	-41	, , ;	7-				
C. Description of monument	for corner and accessoric	es established to perpetuate								······································	;		
CORNER COMMON TO SECTIONS SET 5/8" X 38" REROD WITH 3" C	S 24 & 25 ON TWP, LINE							ORNE	R.				
WITNESSES:	•									IJZ?	Č»		
NORTH 18.00' N&T IN 10" FENCE SOUTH 30.40' N&T IN FENCE COR	POST (OBT) RNER (OBT)						A	THE W	7E C	FM	CI,	C. A.	٠.
N36W 12.80' N&T IN 8" ASH N49E 29.10' N&T IN 4" POPLAR							2 LIO	P	RO. ROFE	NRK I BISC Essic	NS Man		A TOTAL
Signed by Manu	(Clais,					,	EN.S.	e Gara		VEYO Vo. Vasa	i 📑		Š
Surveyor's Michigan License N			Date /2	-20	90	6	, F.	/ 3	G . E	<u> </u>	ر برجيد س	رار در مراکزی	—
										22.36	20	-	