

SURVEY & REMONUMENTATION

MAR 21 1997

COMMISSION

REMONUMENTATION SECTIONS 4, 5, 8 & 9, OLIVE TOWNSHIP LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Located In: Clinton (County) Corner Code # _____

1. Public Land Survey T 6N R 2W E 3
T _____ R _____
T _____ R _____
T _____ R _____

2. Property Controlling S _____ T _____ R _____
In Section S _____ T _____ R _____

3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

SURVEY & REMONUMENTATION
I, Arden S. Pierson, P.S., in a field survey on August 13, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- ♦ Original survey by Hervey Parke, DS, 1826. Set Post Corner Sections 4, 5, 8 and 9. Witnessed by: B. Ash 22" - N52°W - 17 links; Elm 10" - S69°E - 24 links.
- ♦ LCRC by Clyde Stephens, PS, #3829, dated June 7, 1971, Liber 1, pages 33-34. A "T" iron was found in the centerline of two section line roads (Loomis Road and Price Road). The "T" iron found at the NW corner was left in position witnessed by:
SE corner of concrete bridge wall - N69°34'W - 38.65'
Stephens Engineering tag in power pole - N13°53'E - 63.75'
Stephens tag in 30 inch Oak - N60°40'E - 51.57'

(OVER)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found "T" iron in monument box rings, and accepted as a careful and faithful reestablishment of the position of the original corner. (Centerline Price and Loomis Roads)

*Set Standard Clinton County Monument and monument box.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Section Corner Common to Sections 4, 5, 8 & 9

- *Set Standard Clinton County Monument and monument box.
- Nail & tag #13039 in NW side Telephone Pole - N57°E - 46.58'
- Nail & tag #13039 in NE side Telephone Pole - N78°W - 189.95'
- Nail & tag #13039 in SE side Power Pole - S25°W - 207.06'
- Nail & tag #13039 in NE side Power Pole - S05°E - 199.25'

*Standard Clinton County Monument is a 2½" dia. Steel tube 30" long with a stamped brass cap and a breakaway magnetic base.

Signed by Arden S. Pierson
Surveyor's Michigan License No. 13039

Date August 15, 1996

RECORDED

OCT 11 8 52 AM '96

REGISTER OF DEEDS
CLINTON COUNTY, MICH.
Arden S. Pierson

LIBER 4, PAGE 163

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													



APPROVED BY
CLINTON COUNTY PEER GROUP
DATED 8/21/96
Arden S. Pierson

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1
REVISED MAY 14, 1
REVISED JAN. 1
REVISED OCT. 1

- ◆ Certificates of Survey by James Stephens, PS, #16053, dated September 14, 1971, Liber 1, pages 79-80. "T" iron witnessed by survey tags and nails. Witnesses:
 - Corner of concrete bridge wall - N69°34'W - 38.65'
 - Utility pole - N13°53'E - 63.75'
 - 30 inch Oak - N60°39'30"E - 51.57'
- ◆ Certificate of Survey by Clyde Stephens, PS, #3829, dated November 24, 1971, Liber 1, page 84. "T" iron found at NE Corner Section 8, T6N, R2W, recorded in Liber 1 of Land Corners on pages 47-48.
- ◆ Certificate of Survey by Fred White, PS, #12034, dated October 2, 1975, Liber 1, pages 735-736. SW Corner Section 4, T6N, R2W (Liber 1, page page 33).
- ◆ Certified Survey by James Porter, PS, #19003, dated January 24, 1986, Liber 2, pages 904-905.
- ◆ Certified Survey by Bruce Floyd, PS, #28068, dated September 19, 1986, Liber 2, pages 978-979.