

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Crawford

(County)

Located In

Corner Code #

1. Public Land Survey	T		R	
	T		R	
2. Property Controlling in Section	S 17	T 25N	R 2W	4
	S 17	T 25N	R 2W	8
3. Miscellaneous Property in Section	S	T	R	
	S	T	R	

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 18, 2004 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

4- Frank Arleth P.S. # 21266 Certificate of survey shows he set a 1/2" bar with P.S. cap for this corner.

Wit: 8" J. Pine N45°W 11.60'
20" B. Oak N80°E 27.7'

8- Frank Arleth P.S. #21266 certificate of survey shows he set a 1/2" bar with P.S. cap for this corner.

Wit: 12" B. Oak N70°W 19.5'
10" B. Oak N10°E 10.0'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

4- Found 1/2" capped iron rod P.S. #21266 as set by F. Arleth

8- Found 1/2" capped iron rod P.S. #21266 as set by F. Arleth

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

4- Found 1/2" capped iron rod P.S. #21266

Wit: 12" Oak S87°W 46.48'
7" J. Pine N30°W 11.65'
20" Twin Oak N86°E 27.69'
11" J. Pine S30°E 29.91'
Carsonite post North 1'±

8- Found 1/2" capped iron rod P.S. #21266

Wit: 5" Maple N05°W 4.17'
16" Oak N51°W 20.12'
5" R. Pine S88°E 46.22'
7" Twin Oak N82°W 23.29'
Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

7-6-04

Surveyor's Michigan License No.:

33981

