

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Crawford

(County)

Located In

Corner Code #

1. Public Land Survey	T	25N	R	3W	F-2		
	T		R				
2. Property Controlling in Section	S	4	T	25N	R	3W	4
	S		T		R		
3. Miscellaneous Property in Section	S		T		R		
	S		T		R		

Register of Deeds Stamp & File Number

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on May 3, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

F-2 This position was not established during the original Government Survey.

4- This position was not established during the original Government Survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

F-2 Established the center of Section 4 at the intersection of the North-South and East-West one quarter lines.

4 - Established Northwest corner of the Southwest quarter of the Northwest quarter of section 4 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-2 Set 5/8" x 32" rered with P.S. cap #33981

Wit: 12" J. Pine	S10°W	15.01'
Maple	N88°W	24.55'
12" Oak	S80°W	26.15'
16" R. Pine	N25°E	51.63'

4- Set 5/8" x 32" rered with P.S. cap #33981

Wit: 12" J. Pine	N43°E	11.92'
12" Oak	S45°E	24.50'
15" R. Pine	S32°W	19.25'
4" Oak	S77°W	18.90'

Signed by:

Carl T. Kiiskila

Date:

6/30/05

Surveyor's Michigan License No.:

33981

