

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Crawford

(County)

Located In

Corner Code #

1. Public Land Survey

T

T

R

2. Property Controlling  
in Section

S

4

T

25N

R

3W

1

S

4

T

25N

R

3W

2

3. Miscellaneous  
Property in Section

S

T

R

S

T

R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 3, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

1- Found a P.K. nail set in the center of an East – West paved road.

2- Found a P.K. nail set in the center of an East – West paved road.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

1- Found a P. K. nail set in the center of an East-West paved road that fits B.L.M. instructions for the subdivision of a section.

2- Found a P. K. nail set in the center of an East-West paved road that fits B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1- Set 1/2" x 24" rerod with P.S. cap #33981

Wit: 10" & 12" Oak N 7°W 52.22'  
10" Oak N54°E 62.81'  
1/2" rod South 33.03'  
CTR E-W RD South 1'

2- Set 1/2" x 24" rerod with P.S. cap #33981

Wit: 19" Oak N28°W 46.01'  
8" R. Pine N19°E 55.15'  
8" R. Pine S28°W 50.58'  
1/2" rod South 32.86'  
Pin falls in CTR E-W RD

Signed by:

Carl T Kiiskila

Date:

6/30/05

Surveyor's Michigan License No.:

33981

