

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

| FOR CORNERS OF-- | LOCATED IN-- | CORNER CODE NUMBER |
|--|---|--------------------|
| 1. PUBLIC LAND SURVEY | T. <u> </u> N. <u> </u> R. <u> </u> W. <u> </u> | |
| 2. PROPERTY CONTROLLING IN SECTION <u>33</u> | T. <u>26</u> N. <u> </u> R. <u>3</u> W. <u> </u> | <u>1; 5</u> |
| 3. MISCELLANEOUS PROPERTY IN SECTION <u>33</u> | T. <u>26</u> N. <u> </u> R. <u>3</u> W. <u> </u> | <u>1-4</u> |
| 4. LOT NO. <u> </u> | RECORDED PLAT <u> </u> | |
| 5. PRIVATE CLAIMS <u> </u> | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 30, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on April 30, 1976, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 1 Set by standard survey procedure for the subdivision of sections.
- 5 Set by standard survey procedure for the subdivision of sections.
- 1-4 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

| | | |
|--|-----------------------------------|-----------------------------------|
| 1 | 5 | 1-4 |
| Set 3' of 1½" pipe (o.d.) & red-top post | Set 3' of 1½" pipe & red-top post | Set 2' of 1½" pipe & red-top post |
| 8" Twin W. Oak N22°E 30.3 | 5" W. Oak N52°W 17.1 | 9" R. Oak S05°W 12.3 |
| 9" Twin W. Oak N77°E 32.1 | 8" R. Oak N50°E 2.5 | 4" R. Oak N88°W 8.7 |

SIGNED BY Kenneth J. Ostling DATE 7/2/76

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1978

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

CRAIGFORD Co