

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

orners in
Crawford
(County)

Located In: Corner Code J-11

Public Land Survey T 27N R 1W

T R

T R

T R

Property Controlling S T R

Section S T R

Miscellaneous S T R

Property in Sec. S T R

STATE OF MICHIGAN
COUNTY OF CRAWFORD

FILED FOR RECORD THIS
6th DAY OF June, 1990 AT
9:30 am/pm, IN LIBER 2
PAGE 366.

Elizabeth D. Wisland
Register of Deeds

Register of Deeds Stamp & File Number

ot No. , Recorded Plat
Private Claims

Norman C. Caldwell in a field survey on March, 19 90,
reby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
as 1 and 2 above were in conformance with regulations and rules therefore as required in the
nt manual of survey instructions of the United States Department of the Interior, Bureau of Land
gement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
of Law; established, re-established, monumented, re-monumented, recovered, found as
ssed below:

E: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

Description of original monument and accessories and/or subsequent restoration:

- 11) Post set by Pettibone, July 23, 1852.
Spruce Pine 9" N01°W .14 (9.24')
Spruce Pine 9" N31°W .23 (15.18')

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 11) LaGuire, 1934, placed pipe & conc. block mon. from orig. BTs.
Arleth, LS 21266, fnd. mon. April 26, 1978.
SW 3.05' 8" J. Pine stump
N82°E 52.2' 6" Oak
S85°W 60.5' 8" J. Pine
rec. in L. 168, pg 221.

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- 11) 1/4 cor. 26&35, T27N-R1W
Fnd. 2" pipe w/conc. block by "LaGuire", reportedly
from orig. BTs. And is accepted as a careful & faithful
perpetuation of the position of the original corner.
North 1' Carsonite Witness Post
East 52.5' 10" Oak (R)
West 60.5' 10" J. Pine (R) dead
S35°E 13.1' 10" J. Pine
S50°W 36.1' 14" Oak

Norman C. Caldwell
ed by

Date April 26

veyor's Michigan License No. 12018

FORM APPROVED BY MICHIGAN SURVEYOR

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2				
3													
4	7		8		9		10		11		12		
5													
6	13		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

