

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Crawford (County)	Located In	Corner Code #
1. Public Land Survey	T 28N R 3W	J-10
2. Property Controlling in Section	S T R	
3. Miscellaneous Property in Section	S T R	

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on January 6, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

J-10 Center 1/4 Corner Section 26, T28N,R3W.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

J-10 Center 1/4 Corner Section 26, T28N,R3W.

Found a standard Crawford County monument flush with ground surface with an orange Carsonite post 1.5' South. Accepted found standard Crawford County monument as the best available evidence of the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-10 Center 1/4 Corner Section 26, T28N,R3W.

Standard Crawford County monument  
 Wit: S25°E 15.83' to set N&T at old nail on E side 8" W.Pine  
 N53°W 33.38' to set N&T on NE side 5" Maple  
 N04°E 38.14' to set N&T on E side 10" Beech  
 N89°E 40.24' to set N&T on S side 30" Maple



Signed by:

Carl T. Kiiskila

Date:

1-6-10

Surveyor's Michigan License No.:

33981