

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Crawford

(County)

Located In

Corner Code #

1. Public Land Survey

T

R

T

R

2. Property Controlling
in Section

S

21

T

28N

R

4W

11

S

21

T

28N

R

4W

12

3. Miscellaneous

Property in Section

S

T

R

S

T

R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on December 5, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

11- Liber 197, page 219, 1980 C. Eugene Ostling R.L.S. #12026 Set 1/2" bar for corner. No witnesses given.

12- This corner position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

11- Found 1/2" bar with R.L.S. cap #12026 fitting C. Eugene Ostling survey of section 21.

12- Established the Northwest corner of the Southwest quarter of the Southeast quarter of section 21 per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

11- Placed P.S. Cap #33981 on found 1/2" iron

Wit: 6" Maple	N24°E	6.85'
8" Maple	S51°E	36.30'
8" Maple	N51°W	11.51'
8" Elm	S28°W	32.80'
Blue Carsonite post	North	1'±

12- Set a 5/8" x 32" rerod with P.S. Cap #33981

Wit: 10" Maple	S89°W	22.16'
10" Basswood	N01°E	19.82'
12" Maple	N83°E	31.40'
6" Maple	S46°E	12.80'
1/2" iron rod	S02°E	1.60'
Blue Carsonite post	North	1'±

Signed by:

Carl T. Kiiskila

Date:

12/20/05

Surveyor's Michigan License No.:

33981

