

SURVEY & REMONUMENTATION

FEB 22 2001

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
REGISTERED

96 DEC 11 PM 3:02

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Charles M. Bosson
REGISTER OF DEEDS

For corners in
Charlevoix

(County)

Located In:

Corner Code #

1. Public Land Survey

T 32N R 7W

D-1 ✓

T 33N R 7W

D-13

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Wayne E. Boss

OCTOBER 18

19 96

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-1 GLO JUNE 1939
JOHN HODGSON ,
SET ¼ SECT. POST
1. BEECH 7 N59W 17
2. BEECH 7 W11E 23

NO TIMBER FOR BEARING TREES.
3. SCHOOL HOUSE S46E 129

E.K. ROBINSON MAY 1895 SET ¼
POST MIDWAY BETWEEN C-1 &
E-1 T32N-R7W

½" IR. SET BY UNKNOWN. J.FERGUSON
WITNESSED COR. IN MAY 1994
6. FENCE POST NORTH 1.25'
7. FENCE POST WEST 0.85'
8. 12" BASSWOOD S80E 19.54'
9. 7" POPLAR S32W 65.00'

W. MILLER AUG. 1883
SET ¼ POST MIDWAY
BETWEEN SEC. CORNERS

4. APPLE TREE 4 N56W 55 ½
5. CHERRY TREE 4 N57½E 56 ½

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-1 FOUND ½" IRON
7. FENCE POST NORTH 1.25'
8. FENCE POST WEST 0.85'
9. 12" BASSWOOD S80E 19.54'
10. 7" POPLAR S32W 65.00'

Charlevoix Co. Surveyor

APPROVED

Signature *Mary C. Fendt*

Date: 11/13/96

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-1 & D-13 D-1 T32N-R7W CORNER COMMON TO D-13 T33N-R7W

CHARLEVOIX CO. MON. SET
7. FENCE POST NORTH 1.25'
8. FENCE POST WEST 0.85'
9. 12" BASSWOOD S80E 19.54'
10. 7" POPLAR S32W 65.00'

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT OF THE ORIGINAL CORNER

igned by

Surveyor's Michigan License No.

20703

LIBER

003 PAGE

Date

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

This should have been entered
the last time

