

FEB 22 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF CHARLEVOIX  
REGISTERED PROFESSIONAL SURVEYOR

96 DEC 11 PM 3:03

For corners in  
Charlevoix

Located In:

Corner Code #

*Charles M. Belen*  
REGISTER OF DEEDS

1. Public Land Survey

T 32N R 7W

F-1

T 33N R 7W

F-13

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5				4		3		2		1	
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Wayne E. Boss, in a field survey on OCTOBER 22, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F-1 GLO JUNE 1839  
JOHN HODGSON,  
SET ¼ SEC. CORNER  
1. BEECH 8 N18W 27  
2. BEECH 8 N26E 31  
  
E.A. BELLENBAUM MSHD  
STATED HE FOUND 4" SQ.  
WOOD STAKE. REPLACED  
  
IT WITH POINTED STONE.  
3. 5" ASH N37W 17.45'  
4. 5" ASH S10E 6.45'  
STONE FD. & USED BY B.JONES  
IN A 1987 SURVEY.  
3. 12" IRONWOOD N35W 17.7  
(STATED AS S.E.)  
4. 8" IRONWOOD S15E 6.5'  
5. S35W 16" MAPLE 18.5'

6. N13E 12" POPLAR 26.95'  
J.FERGUSON SEPT. 1987 SET ½ IR. LCRC  
L.2, P. STATING HE USED POSITION ES-  
TABLISHED BY CHX.ABST. & ENG. IN  
NOV. 1979.  
7. 6" POPLAR N80E 6.72'  
8. 10" ASH S54E 29.28'  
9. 7" POPLAR S38W 18.65'  
10. 8" POPLAR N48W 11.91'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-1 FD. ½ " FERGUSON IR. AND FD. BELLENBAUM POINTED STONE. BELLENBAUM STATED HE FOUND A 4" SQ. POST AND REPLACED THE POST WITH THE POINTED STONE. WE CAN FIND NO RECORD OF THAT 4" SQ. POST HAVING BEEN SET AS THE ¼ COR. THE FERGUSON IRON FITS, THE OLD FENCE REMENENTS TO THE NORTH, FITS THE ROAD LOCATION, FITS GOOD WITH E-1 & G-1 BUT ALSO FITS BETTER WITH F-4 & WITH F-12 133N-R7W. THE FERGUSON/CHX. ABST. & ENG. LOCATION MOST ACCURATELY FITS THE ORIGINAL LOCATION.  
7. 6" POPLAR N80E 6.72'  
8. 10" ASH S54E 29.28'  
9. 7" POPLAR S38W 18.65'  
10. 8" POPLAR N48W 11.91'  
11. N15W 34.1' BELLENBAUM POINTED STONE.


Charlevoix Co. Surveyor  
APPROVED  
Signature *Mary C. Ferrell*  
Date: 11/13/96

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-1 & F-13 F-1 T32N-R7W COMMON CORNER TO F-13 T33N-R7W

7. 6" POPLAR N80E 6.72'  
8. 10" ASH S54E 29.28'  
9. 7" POPLAR S38W 18.65'  
10. 8" POPLAR N48W 11.91'  
11. N15W 34.1' BELLENBAUM POINTED STONE

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER



Signed by *Wayne E. Boss*

Date 11/29/96

Surveyor's Michigan License No. 20703 LIBER 003 PAGE 78

*This should have been entered  
in the book twice*