

FEB 22 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

CHANDLER TOWNSHIP

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
REGISTERED RECORD

00 DEC -8 PM 12: 24

Caroline M. Dutton
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

CHARLEVOIX
(County)

Located in:

Corner Code #

1. Public Land Survey

T 33N R 4W

A-5

T R

~~T 33N R 50~~ 115 ✓

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, JAMES E. EVANS, in a field survey APRIL 5, 2000 do hereby state that requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		6		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

A-5 SECTION CORNER COMMON TO SECTIONS 7 & 18 T33N-R4W AND SECTIONS 12 & 13 T33N-R5W.

GLO: SET POST

Sugar 24" S40E 15 lks (9.90')

Hemlock 24" N50'W 18 lks (11.86')

May 23, 1840

By: John Mullett D. S.

Carl F. Roser PS #12028 LCRC 1-12-1982

Found Schaaf monument from 1930's and replaced with DNR monument and cedar post.

7" Ironwood South 15.1 (1)

3" Twin Maple N30'E 12.7 (2)

4" Maple S75'E 35.0' (3)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner

A-5 SECTION CORNER COMMON TO SECTIONS 7 & 18 T33N-R4W AND SECTIONS 12 & 13 T33N-R5W

Found DNR monument and cedar post

Distance to A-4 2668.51' (GLO = 2640.0' DNR = 2668.58')

Distance to A-6 2658.67' (GLO = 2640.0 DNR = 2658.67' E.A. Robinson = 2677.1)

Charlevoix Co. Surveyor
APPROVED

Signature Mary C. Feindt

Date: Dec 7, 2000


C. Description of monument for corner and accessories established to perpetuate location the position of the corner:

A-5 SECTION CORNER COMMON TO SECTIONS 7 & 18 T33N-R4W AND SECTIONS 12 & 13 T33N-R5W

FOUND DNR MONUMENT AND CEDAR POST

- 7" Ironwood S 2' W 15.26' Set nail & cap #22431 in blaze mark in SW side. (1)
- 9" Twin Maple N 32' E 12.75' Set nail & cap #22431 in blaze mark in South side. (2)
- 6" Maple S 74' E 35.16' Set nail & cap #22431 in blaze mark in SW side. (3)
- 9" Tri Ironwood N 15' W 28.53' Set nail & cap #22431 in East side.

And is accepted as the best available evidence of the position of the original corner.



Signed by [Signature]
Surveyor's Michigan License No 22431

Date 12-07-00