

FEB 22 2001

SECTION

CHANDLER TOWNSHIP

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
RECEIVED FOR RECORD

00 DEC -8 PM 12:25

Charles B. Justice

REGISTER OF DEEDS

Register of Deeds Stamp & File Number

CHARLEVOIX
(County)

Located in:

Corner Code #

1. Public Land Survey

T 33N R 4W A-6
T R
T 33N R 5W M-6
T R
T R
T R
T R
T R
T R

2. Property Controlling

S T R
S T R
S T R
S T R

3. Miscellaneous

S T R
S T R

Property in Sec.

S T R

Lot No. Recorded Plat

Private Claims

JAMES E. EVANS, in a field survey APRIL 5, 2000 do hereby state that requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current annual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors by a Decree of a Court of Law; established, re-established, monumented, recovered, found expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Description of original monument and accessories and/or subsequent restoration:

A-6 QUARTER CORNER COMMON TO SECTION 18 T33N-R4W AND SECTION 13 T33N-R5W

3LO: SET QUARTER SECTION POST

Ironwood 6" N60°E 28 lks (18.48')

Beech 18" S25°W 12 lks (7.92')

May 23, 1840

by: John Mullett D. S.

Carl F. Roser PS #12028 LCRC 1-12-1982

Found Schaaf pipe monument and replaced with DNR monument and cedar post

5" Maple S05°E 4.8' (1)

5" Maple N80°E 14.2 (2)

6" Maple N35°W 22.9 (3)

Description of corner evidence found and/or method applied in restoring or reestablishing corner

A-6 QUARTER CORNER COMMON TO SECTION 18 T33N-R4W AND SECTION 13 T33N-R5W

Found DNR monument and cedar post. 30 feet North of old logging road.

Distance to A-5 2658.67' (GLO = 2640.0' DNR = 2658.49' E. A. Robinson = 2677.1')

Distance to A-7 2627.25' (GLO = 2640.0' DNR = 2627.17' E. A. Robinson = 2645.9')

Charlevoix Co. Surveyor

APPROVED

Signature *Mary C. Feendt*

Date: *Dec 7, 2000*

Description of monument for corner and accessories established to perpetuate location the position of the corner:

A-6 QUARTER CORNER COMMON TO SECTION 18 T33N-R4W AND SECTION 13 T33N-R5W

FOUND DNR MONUMENT AND CEDAR POST

6" Maple S 01° E 4.69' Set nail & cap #22431 in blaze mark in North side. (1)

5" Maple N 82° E 14.56' Set nail & cap #22431 in blaze mark in North side (2)


6" Maple N 34° W 22.80' Set nail & cap #22431 in blaze mark in SW side (3)

9" Maple N 63° E 12.85' Found blaze mark in West side.

4" Ironwood S 58° E 30.34' Set nail & cap #22431 in North side.

6" Maple S 50° E 3.23' Found blaze mark on North side.

10" Tri Maple N 78° W 22.80' Set nail & cap #22431 in South side.



And is accepted as the best available evidence of the position of the original corner.

Witnessed by *[Signature]*
Surveyor's Michigan License No 22431

Date 12-07-00